



UNIVERSAL ELECTRIC MOTORS

COOLING MOTOR CATALOGUE

NEW THIS SEASON

- ✓ EXPANDED RANGE OF OEM REPLACEMENTS
- ✓ MORE ENERGY EFFICIENT MOTORS ADDED
- ✓ MANY NEW FAN COIL MOTORS
- ✓ NEW ECM OEM REPLACEMENTS
- ✓ 70°C AMBIENT 575 VOLT CONDENSER FAN MOTORS
- ✓ 575 VOLT 825 RPM CONDENSER FAN MOTORS
- ✓ EXTENDED RANGE OF VARIABLE SPEED DRIVES



OMNIDRIVE®



WE DO MOTORS BEST.



www.uem.ca



Ultimate Truck Stock Motor™

Features:

- Suitable for Evaporator & Condenser Applications
- IP66 Water Tight with all angle Moisture Protection
- High Efficiency (up to 65%)
- Includes Plug, Speed Nut, Rubber Isolator
- Universal Mounting
- UL/CUL Approved
- Aluminum Frame
- Thermally Protected
- Robust Ball Bearing System
- Replaces: Hussmann, Copeland, Tecumseh, Hill, Tyler, Kysor, Crystal Tips & More..

4 to 25 Watts!



▲ Std 3-hole style
 ■ Hussmann 4-hole



Dual Side Bosses

Refrigeration ECM



Stock #	Encl.	Watts	Volts	Amps.	RPM Range	Bearings	Shaft	Rotation
EC5411	IP66	4 - 25	115	0.20 - 0.75	1550 - 1775	Ball	Hubless	CWOSE
EC5412	IP66	4 - 25	115	0.20 - 0.75	1550 - 1775	Ball	Hubless	CCWOSE

Cross Reference

	Rotom	Morrill	Century
EC541	04-R6711, 04-R6811 04-R9211, 04-R5444	5R016, 5R024, 5R025, 5R020, 5R021	9207F2, 9208F2 9211, 9212, 9213
EC5412	Not Available	Not Available	Not Available

Kit Sold Separately



Kit 58

EC5411
EC5412

Replaces 51 Frame

Converts 2-pin Straight to 2-pin 90 Degree




Part No. 2117

Features:

- Cast Iron Construction
- Dual Side Bosses
- 2-pin Lyall Plug Included
- Up to 65% Efficiency
- Standard 3 Hole & 4 Hole (Hussmann Style Mount)
- Replaces 6, 9, 12, 14, 15 & 16 Watt P.S.C. & Low Efficiency Shaded Pole Motors

6 to 16 Watts!



All Models

Refrigeration ECM



Stock #	Encl.	Watts	Volts	Amps.	RPM	Shaft	Rotation	Replaces
9207F2	T.E.	6 - 9 - 12	115	0.20 - 0.30	1550	Hubless	CWOSE	R6711
9208F2	T.E.	14 - 15 - 16	115	0.47 - 0.58	1550	Hubless	CWOSE	R6811

Features:

- Up to 70% Efficiency
- Mounting Shroud & Fan Guard Mounting With Four Extended M4 Threaded Thru-Bolts on Motor Shaft Side
- Reduce Inventories, One Motor Covers 4W Through 16W Applications
- Energy & Cost Saving, Payback In Less Than One Year
- CO² Reduction, Eco-Friendly Technology
- Drop In Replacement For Traditional Shaded Pole Unit Bearing Motors
- ECR Motors Are Ideal For Retrofit & New Installations
- Clockwise Opposite Shaft End Rotation, 19" Sleeved Leads With 2 Pin Plug
- Rear Mounting With Three Standard 8-32 UNC Threaded Holes
- Foot Mounting With 4 Threaded 8-32 UNC Holes
- Universal Hubless Shaft Accommodates Standard Axial Fan Blades
- Moisture & Humidity Resistant
- Input Voltage Range For ECR161 Motor Is 90V...140V
- Operating Temperature Range of -10°C to +40°C (14°F to 104°F)
- Automatic Thermal Overload/Electronic Protection
- Fully Enclosed, Long Life Ball Bearings

4 to 16 Watts!



ECR161

Refrigeration ECM



Stock #	Encl.	Watts	Volts	Amps.	RPM	Shaft	Rotation	Replaces
ECR161 •	T.E.A.O.	16 Max.	115	0.34	1800	Hubless	CWOSE	Many OEM

Features:

- Open Fan Cooled
- Shaded Pole Design
- Sleeve and Ball Bearings



G.E. 11 Frame Replacements



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
9660	O.F.C.	1/20	115	2.00	1550	5/16" x 2.00"	CWOSE	GE-1331
9661	O.F.C.	1/20	115	2.00	1550	5/16" x 2.00"	CCWOSE	GE-1341
9662	O.F.C.	1/20	208-230	1.00	1550	5/16" x 2.00"	CCWOSE	GE-1342
9663	O.F.C.	1/20	208-230	1.00	1550	5/16" x 1-1/4"	CWOSE	GE-1016
9664	O.F.C.	1/20	208-230	1.00	1550	5/16" x 2.00"	CWOSE	GE-1332
9336 ●	O.F.C.	1/20	230	1.10	1550	5/16" x 2-5/8"	CWOSE	GE-1336
SS1332 ●	O.F.C.	1/20	208-230	1.10	1550	5/16" x 2.00"	CCWSE	GE-1332
SS671 ●	O.F.C.	1/15	115/208-230	2.10/1.10	1550	5/16" x 2.00"	CCWSE	GE-1231
SS672 ●	O.F.C.	1/15	115/208-230	2.10/1.10	1550	5/16" x 2.00"	CWSE	GE-1441
9665	O.F.C.	1/15	208-230	1.00	1550	5/16" x 1-1/4"	CWOSE	GE-1232
671B ●	O.F.C.	1/15	115/208-230	2.10/1.10	1550	5/16" x 2.00"	CWOSE	GE-1231
672B ●	O.F.C.	1/15	115/208-230	2.10/1.10	1550	5/16" x 2.00"	CCWOSE	GE-1441
981	O.F.C.	1/15	460	0.60	1550	5/16" x 2-1/2"	CCWSE	810F050B

Pedestal Fan Air Circulator Motors

Features:

- Yoke Mount - Extended Through Bolts
- Totally Enclosed, Air Over
- Thermally Protected
- Pull Chain
- 10' Cord & Plug
- 40°C Ambient
- Sealed Ball Bearings



All Models

48 Frame - Two Speed



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS486 ●*	T.E.A.O.	1/4	115	3.40	1100 / 2	1/2" x 3.00"	REV.	General Replacement
SS647 ●*	T.E.A.O.	1/3	115	4.40	1100 / 2	1/2" x 3.00"	REV.	General Replacement

Features:

- Shaded Pole Design
- Cast Iron Construction
- Totally Enclosed



All Models

Unit Bearings



Stock #	Encl.	Watts	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS5211	T.E.	4	115	0.29	1550	Hubless	CWLE	EE5211
SS5311	T.E.	6	115	0.40	1550	Hubless	CWLE	EE5311
SS5411	T.E.	9	115	0.55	1550	Hubless	CWLE	EE5411
SS5611	T.E.	9	115	0.55	1550	Hubless	CWLE	EE5611
SS5811	T.E.	16	115	1.00	1550	Hubless	CWLE	EE5811

Features:

- Shaded Pole Design
- Cast Iron Construction
- Open Enclosure



250 - 252 - 254 - 256



258 - 260



276

Unit Bearings



Formerly A.O. Smith Electrical Products Company

Stock #	Encl.	Watts	Volts	Amps.	RPM	Shaft	Rotation	Replaces
250	O.O.S.E.	25	115	1.10	1500	Hubless	CWLE	R2511
252	O.O.S.E.	25	230	0.60	1500	Hubless	CWLE	R2512
254	O.O.S.E.	35	115	1.40	1500	Hubless	CWLE	R3511
256	O.O.S.E.	35	230	0.70	1500	Hubless	CWLE	R3512
258	O.O.S.E.	50	115	1.70	1500	3/8" x 1-1/2"	CWLE	R5011
260	O.O.S.E.	50	230	0.85	1500	3/8" x 1-1/2"	CWLE	R5012
276	O.S.E.	50	230	0.85	1500	5/16" x 2-1/2"	CCWLE	R5122

Features:

- Impedance or Thermally Protected
- Continuous Duty, Air Over
- Mechanically Reversible
- Class 'B' Insulation



'C' Frame Skeleton®

OMNIDRIVE®

Stock #	Stack	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS617	3/8	208-240	0.22	1900	3/16"x 1-1/4"	CWSE	R617
SS635	1-1/2	208-240	120/0.83	1550	1/4" x 1-1/12"	CCWSE	R635
SS3670	5/8	120/240	0.40/0.26	3000	3/16" x 1-9/16"	CWSE	R3670
SS3100	5/8	115	0.59	3000	7/12" x 1-11/16"	CCWSE	R3100, C01550 EM550, VFM100 SM550, C65878

Evaporator Fan Motors

Features:

- Open & Totally Enclosed Construction
- Shaded Pole & P.S.C. Design
- Sleeve and Ball Bearings



3.3" Diameter

OMNIDRIVE®

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS101	T.E.	1/45	115	0.90	1550	Hubless	CCWSE	R101
SS103	T.E.	1/45	115	0.90	1550	Hubless	CWSE	R103
SS313 ●	OPEN	1/15	115	2.20	1550	5/16" x 3.00"	CWSE	R313
SS358	OPEN	1/20	115	2.00	1550	5/16" x 3.20"	CWSE	R358
SS359	OPEN	1/20	230	1.10	1550	5/16" x 3.20"	CWSE	R359
SS360	OPEN	1/30	115	1.20	1550	1/4" x 1.75"	CCWSE	R360
SS368	OPEN	1/20	115	1.80	1550	5/16" x 2.80"	CCWSE	R368
SS369	OPEN	1/20	230	0.95	1550	5/16" x 2.75"	CCWSE	R369
SS370 ●*	OPEN	1/20	115	0.80	1550	5/16" x 2.80"	CCWSE	R370
SS371 ●*	OPEN	1/20	230	0.30	1550	5/16" x 2.80"	CCWSE	R371
SS574	OPEN	1/20	120	1.90	1550	5/16" x 2.50"	CCWSE	R90574
SS575	OPEN	1/20	208-230	0.89	1550	5/16" x 2.50"	CCWSE	R90575
SS9721 ●*	OPEN	1/12	115/208-230	1.10 / 0.60	1550	5/16" x 3.15"	REV.	R90721




Ultimate Truck Stock Motor™

Features:

- High Efficiency P.S.C. Design
- Uses Over 40% Less Electricity than Shaded Pole Designs
- Four 8-32 x 3/4" Stud Extensions at each end
- Automatic Reset Thermal Overload Protector
- Capacitor Included
- Reversing Leads
- Ball Bearings have all Angle Thrust System
- 15" Cord & Plug (0.250" pin pitch) Includes Adapter for 0.375" pin pitch



All Models



3.3" Diameter




Stock #	Incl.	HP	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
EM-9662	● * OPEN	1/20	115	0.85	1550	3.26"	5/16" x 3.00"	REV.
EM-9656	● * OPEN	1/15	208-230	0.48	1550	3.78"	5/16" x 3.00"	REV.

Cross Reference

	Rotom	Bohn Century	Fasco
EM-9662	R90721, R358, R1052, R368 R90572, R90574	5001L, 5008S, 5004L574A, 574 5034L, 5034LS, 5008SS	D1124, D1101
EM-9656	R90721, R359, R1053, R369 R90573, R90575, R91125	7190-0442, 25309101573A, 575 5008T, 5034M, 5034MS 5008TS	D1126, D1125, D1103 D1122, D1123

	Blanchard-Ness	Larkin Packard	Ref Plus
EM-9662	E1052	253-1194, 2530910141101, 41154, 45036 7163- 2113, JA2N015N41124, 45008S, 49101	RMT0011
EM-9656	E1053	253-1195, 2530910141103, 41195, 41126 7163-3371, 7163-213545008T, 41125, 49101 JA2N016N	RMT0012



● Ball Bearing (*) P.S.C. Design

ECM Evaporator Fan Motors

Energy Efficient Electronically
Commutated Brushless DC Motors



www.uem.ca

Features:

- Up to 70% Efficiency
- Energy & Cost Saving, Payback In Less Than One Year
- CO² Reduction, Eco-Friendly Technology
- Drop In Replacement For Traditional Shaded Pole & P.S.C. Evaporator Fan Motors
- Flexible Mounting With Four Extended 8-32 UNC Threaded Thru-Bolts on 2.84" B.C.D. at Both Ends
- Clockwise Shaft End Rotation, 19" Sleeved Leads With 2 Pin Plug
- Standard 5/16" Shaft Diameter, 2-1/2" Length With 1-3/4" Flat
- Moisture & Humidity Resistant, IP42 Enclosure Rating
- Operating Temperature Range of -30°C to +40°C (-22°F to 104°F)
- Input Voltage Range For ECR501 Motor is 100V...127V ECR502 Motor is 190V...254V
- Fully Enclosed, Long Life Ball Bearings
- Automatic Thermal Overload/Electronic Protection



All Models

3.3" Diameter

OMNIDRIVE®

Stock #	Encl.	Watts	Volts	Amps.	RPM	Shaft	Rotation	Replaces
ECR501	T.E.A.O.	50	115	1.13	1550	5/16" x 2-1/2"	CWSE	Many OEM
ECR502	T.E.A.O.	50	208-230	0.67	1550	5/16" x 2-1/2"	CWSE	Many OEM

Features:

- 4 Bolts on Shaft End on 2.86" B.C.D.
- Lyall Plug Included
- Up to 65% Efficiency
- Replaces Heatcraft, Bohn, Larkin, Chandler & Climate Control ECM Evaporator Motors

ECM Evaporator Fan Motors



All Models

42 Frame



Formerly A.O. Smith Electrical Products Company

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
9215L	T.E.	1/15, 1/20, 1/25	115	1.20	1625	5/16" x 2.90"	CWSE	22617801, 22618001 25307801, 25308001
9215H	T.E.	1/15, 1/20, 1/25	230	0.70	1625	5/16" x 2.90"	CWSE	22617701, 22617901 25307701, 25307901

Features:

- Shaded Pole Design
- Sleeve Bearings
- Replacements for Reversomatic & Intercity



SS630



SS260 - SS262- SS264



SS266



SS2603 - SS2604



SS2605



SS2609 - SS2612

OEM Replacements



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS630	OPEN	---	120	0.75	3000	7/32" x 1-13/16"	CCWSE	R630
SS260	T.E.	1/90	115	0.60	1500	5/16" x 1.09"	CCWSE	R260
SS262	T.E.	1/40	115	1.10	1550	5/16" x 1-1/2"	CCWSE	R262
SS264	T.E.	1/75	120	0.70	1550	5/16" x 2.06"	CCWSE	R264
SS266	T.E.	1/20	120	1.45	1550	5/16" x 1.40"	CCWSE	R266
SS2603	OPEN	1/35	115	1.15	1550	1/2" x 2.10"	CCWSE	R2603
SS2604	OPEN	1/10	120	2.65	1550	1/2" x 2.05"	CCWSE	R2604
SS2605	OPEN	1/12	115	3.00	1050	1/2" x 1.98"	CCWSE	R2605
SS2609	T.E.	1/30	115	1.21	1550	1/2" x 2.35"	CCWSE	R2609
SS2612	T.E.	1/30	115	1.21	1550	1/2" x 2.35"	CWSE	R2612

Fan Coil Motors

Features:

- P.S.C. Design
- Capacitor Included
- Sleeve Bearings
- Replacements for Temspec, Unilux, Climetec & Snyder-General



All Models

42 & 48 Frame



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS799 *	OPEN	1/8	115	2.10	1000/5	1/2" x 5.00"	CWSE	DD-029
SS2799 *	OPEN	1/6	115	2.60	950/5	1/2" x 4.40"	CWSE	DD-030

(*) P.S.C. Design



ECM Fan Coil Replacement

Features:

- Energy Efficient ECM Technology
- ECM with Internal Control
- Up to 65% Efficiency vs. Low Efficiency Shaded Pole
- Rotors are Isolated from Shaft to Reduce Motor Vibration
- Saves an Average of 69% on Energy Usage
- Double Shaft
- Open Construction
- Resilient Base
- 54" Leads
- Runs Cooler
- Easy to Install
- Long Life Ball Bearings





42 Frame ECM



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation
CS89 •	OPEN	1/10	115	1.56	1100/3	9.30" x 1/2" x 9.30"	CWLE

Replaces many Shaded Pole & P.S.C. Motors
In Fan Coil, PTACS & Air Conditioners



Features:

- Shaded Pole & P.S.C. Design
- Open & Totally Enclosed
- 60 Hz
- Sleeve Bearings
- Thermally Protected



EC6W115 - EC9W115
EC16W115 - EC16W230
EC34W115 - EC34W230




RMT0004E - RMT0005E



ECFC1586 - ECFC1616
ECFC1617



ECFC7004



ECFC1893 - ECFC1895



Stock #	Watts	HP	Volts.	Amps.	RPM	Shaft	Rotation
EC9W115	6	---	115	0.41	1550	Hubless	CCWSE
EC9W115	9	---	115	0.58	1550	Hubless	CCWSE
EC16W115	16	---	115	0.89	1550	Hubless	CCWSE
EC16W230	16	---	230	0.50	1550	Hubless	CCWSE
EC34W115	34	---	115	1.60	1550	Hubless	CCWSE
EC34W230	34	---	230	0.80	1550	Hubless	CCWSE
RMT0004E •	34	---	115	1.60	1550	Hubless	CCWSE
RMT0005E •	34	---	230	0.80	1550	Hubless	CCWSE
ECFC1586 •*	41	1/20	115	1.07	1550/2	1/2" x 3-29/32"	CWSE
ECFC1616 •*	---	1/8	115	2.16	1550/2	1/2" x 3-3/4"	CWSE
ECFC1617 •*	---	1/4-1/8	115	2.52/1.22	1090	1/2" x 3-1/2"	CWSE
ECFC1893 •*	50	1/15	115	0.82	1550/6	7-3/4" x 1/2" x 7-3/4"	CWSE
ECFC1895 •*	420	1/4	115	3.60	1550/6	8-7/16" x 1/2" x 8-7/16"	CWSE
ECFC7004 •*	40	1/15	115	0.93	1550/2	5/16" x 1-7/16"	CCWSE



Fan Coil Motors

42 Frame




Stock #	Encl.	HP	Volts.	Amps.	RPM	Shaft	Rotation
320	OPEN	1/15	208-230	1.30	1050/3	8-7/8"x1/2"x8-7/8"	DBL
362 *	OPEN	1/10	115	1.70	1075/4	10-11/16"x1/2"x10-11/16"	DBL
381 *	OPEN	1/10	208-230	0.81	1075/3	10-11/16"x1/2"x10-11/16"	DBL
953 *	OPEN	1/15	115	0.80	1100/3	10-1/2"x1/2"x10-1/2"	DBL
945A *	OPEN	1/8	115	1.20	1500/3	9"1/2"x7-1/2"	DBL
UE955 *	OPEN	1/6	115	2.30	1500/3	10-1/2"x1/2"x10-1/2"	DBL
954 *	OPEN	1/30	115	0.60	1100/3	1/2" x 8-1/2"	CCWSE
9608 *	OPEN	1/20	115	0.60	1100/3	1/2" x 9-1/2"	REV
SS362 *	OPEN	1/10	115	1.80	1050/4	10-1/2"x1/2"x10-1/2"	DBL
SS362S *	OPEN	1/10	115	1.80	1050/4	10-1/2"x3/8"x10-1/2"	DBL

(•) Ball Bearing (*) P.S.C. Design

Features:

- Shaded Pole & P.S.C. Design
- Capacitor Included
- Open Air-Over Design
- Wiring Harness w/Plug Supplied
- Long Life Self Aligning Sleeve & Sealed Ball Bearings



OEM Replacements



Stock #	Diameter	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
56342	3.3"	1/70	115	1.00 / 0.50	1550/2	3/8" x 5-1/2"	CWSE	56342-0
56343	3.3"	0.27	115	1.32	1550/2	3/8" x 5-3/4"	CWSE	56343-0, JA2M414
56344 ●*	3.3"	0.08	115	1.60 / 1.00	1550/2	3/8" x 4.75"	CWSE	56344-0, JE2H047
56345 *	3.3"	1/25	115	1.00	1050	3/8" x 4.75"	CWSE	56345-0
56346 ●*	3.3"	0.27	115	3.20 / 1.90	1550/2	3/8" x 5.50"	CWSE	56346-0, JE2K007
56347 ~*	3.3"	1/12	115	1.60	1050	6.10" x 3/8" x 6.10"	CCWLE	56347-0
56348 ~	5.0"	1/10	115	3.90	1050	6-1/4" x 1/2" x 6-1/4"	CCWLE	56348-0
60024	3.3"	1/30	115	1.40	1550	5/16" x 1-1/2"	CWSE	60024-0
60030	3.3"	1/80	115	0.74	1400	1/4" x 1-3/4"	CWSE	60030-0
60076 ●*	5.5"	1/6	115	3.40	1300/2	1/2" x 2.65"	CWSE	60076-0
63699 ●*	5.5"	1/4	115	3.40	1725	1/2" x 4.77"	CWSE	63699-0
63745 *	3.3"	1/30	115	0.50 / 0.40	1550/2	3/8" x 3.69"	CWSE	63745-0
63746 ●*	3.3"	1/12	115	1.50 / 0.90	1550/2	3/8" x 3.40"	CWSE	63746-0, JE2H057
63747 *	4.4"	1/7	115	2.50	1550/3	1/2" x 2.20"	CWSE	63747-0
63748 *	4.4"	1/6	115	1.80	1550/3	1/2" x 2.60"	CWSE	63748-0
63749 ●*	5.5"	1/4	115	2.80	1725	1/2" x 3.00"	CWSE	63749-0
63750 ●*	5.5"	1/3	115	4.00	1550/3	1/2" x 5.55"	CWSE	63750-0
63751 ●*	5.5"	1/2	120	5.00	1650/2	1/2" x 5.50"	CWSE	63751-0
63752 ● *	5.5"	3/4	115	8.60 / 9.60	1625	1/2" x 5.33"	CWSE	63752-0
63821 ●*	5.0"	1/4	115	2.70	1550	1/2" x 2.60"	CCWSE	63821-0



OEM Replacements

OMNIDRIVE®

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
11811*	OPEN	1/6	120	2.10	1630/2	3/8"x1.90"	CCWSE	Venmar/VanEE
12026 ~•*	OPEN	1/8	120	1.89	1630/3	2.93"x3/8"x2.93"	CWLE	Venmar/VanEE
12027 ~*	OPEN	1/12	120	1.20	1625/3	3.50"x3/8"x3.56"	CWLE	Venmar/VanEE
SS348 *	OPEN	1/15	115	1.30	1550/2	3/8"x3.00"	CWSE	Venmar/VanEE
SS438 *	OPEN	1/14	115	1.46	1625/2	5/16"x1.88"	CCWSE	Venmar/VanEE
SS462 ~*	OPEN	1/12	120	1.20	1625/2	3.50"x3/8"x3.56"	CWLE	Venmar/VanEE
950-1020	OPEN	1/25	115	1.37	3000	5/16"x2-1/4"	CCWSE	Tjernlund
950-1021 *	OPEN	1/7	115	1.50	3300	3/8"x2.25"	CCWSE	Tjernlund
950-1022 •*	OPEN	1/5	115	2.80	1700	1/2"x3.40"	CCWSE	Tjernlund
950-3022	OPEN	1/50	115	1.00	1600	5/16"x4-1/8"	CWSE	Tjernlund
SS2224	OPEN	1/114	115	0.75	1500/2	3/8"x2-3/4"	CWSE	Loren Cook
SS2497	OPEN	1/10	115	3.40	1100	1/2"x1-5/8"	CWSE	Nutech
SS2655 •*	OPEN	1/12	120	1.34	1550	3/8"x2.82"	CCWLE	Loren Cook
SS3234	OPEN	1/16	115	2.20	1550/2	3/8"x2-1/2"	CWSE	Loren Cook
SS4200	OPEN	1/23	115	1.50	1500	3/8"x2-3/4"	CWSE	Loren Cook
SS5200 *	OPEN	1/16	115	1.50	1500	3/8"x2-1/4"	CWSE	Loren Cook
SS6264	OPEN	1/11	115	4.60	1500/2	1/2"x6-1/4"	CWSE	Loren Cook
SS7274 *	OPEN	1/4	115	3.90	1625/2	1/2"x6-1/4"	CWSE	Loren Cook
SS8313 *	OPEN	1/8	115	2.60	1550/3	1/2" x 2-3/4"	CCWSE	GreenHeck
SS9316	OPEN	---	115	3.40	1100	1/2" x 3-7/8"	CWSE	Broan
30080058	OPEN	---	115	4.30	1100	1/2" x 3-7/8"	CWSE	Broan
30080135 *	OPEN	1/100	115	0.61	1050	5/16" x 1-7/8"	CCWSE	Broan
C06E4A *	OPEN	1/10	120	1.80	1050	1/2" x 2-3/8"	CWSE	Broan
C07E2A *	OPEN	1/8	115	1.40	1600	1/2" x 3.00"	CWSE	Loren Cook
C07E4A *	OPEN	1/6	115	1.80	1100	1/2" x 3.43"	CWSE	Loren Cook
C08E10A •*	OPEN	1/4	115	3.50	1550	1/2" x 4.50"	CWSE	Loren Cook
C09E10A *	OPEN	1/3	115	4.80	1080	1/2" x 3.00"	CCWSE	Loren Cook
C10E10A •*	OPEN	1/2	120	6.20	1500/1300	1/2" x 3.25"	CWSE	Loren Cook

(•) Ball Bearing (*) P.S.C. Design (-) Double Shaft

Features:

- All Angle Mount
- Continuous Duty, Air Over
- Class 'B' Insulation
- Shaded Pole
- Thermally Protected
- Single, Two & Three Speed Models
- Variable Speed Model
- Sleeve Bearings



UB1



UB3



UB265



UB160



UB465



UFB500

3.3" Diameter

OMNIDRIVE®

	Volts	Amps.	RPM	Reference	Replaces
UB1	115	1.20	3000	General Replacement	RB1
UB3	120	0.80	3000	General Replacement	RB3
UB160	115	1.00	1550	General Replacement	RB160
UB265	115	1.86	1630	General Replacement	RB265
UB465	115	2.90	1550/2	General Replacement	RB465
UFB500	120	1.10	2860	Greenhouse	RFB500

Inline Centrifugal Fans

Features:

- Installs in any Position
- High Pressure & Volume
- Supplied with 8 Foot Cord & Plug
- Mounting Bracket Included
- Backwards Inclined Fan Blades
- Steel Housing, Baked Powder Coat Finish
- Permanently Sealed Ball Bearings
- Three Year Warranty



VENT-100 - VENT-315

OMNIDRIVE®


Stock #	Duct Diameter	CFM	Watts	Volts	Amps.	Hz.	dBA
VENT-100 •	4 INCH	175	98	120	0.97	60	1.90
VENT-150 •	6 INCH	435	130	120	0.97	60	1.00
VENT-200 •	8 INCH	745	210	120	1.76	60	1.90
VENT-250 •	10 INCH	785	230	120	2.00	60	1.90
VENT-315 •	12 INCH	1075	295	120	2.50	60	2.60



RESCUE Select®

Features:

- The ECM Aftermarket Motor that Replaces OEM Constant Torque Blower Motors
- Electronically Controlled Brushless Permanent Magnet Motor
- Saves 25% of the Watts in A/C or Heating
- 75% Watt Reduction in Circulation Mode
- A Variety of Mounting Kits are Available
- Electronically Protected Motor
- Continuous Duty, Air Over
- 6000V Surge Protection
- No Capacitor Required
- Voltage 230V or 115V
- Up to 82% Efficiency
- Reversible Rotation
- Class 'B' Insulation
- 2 Year Warranty
- 40°C Ambient
- Ball Bearings



**Replaces Over 900 OEM X13®† and SelecTech®† ECM Motors
Now Customized for You and Shipped Same Day from Stock !**

48 Frame



Stock #	Encl.	HP Range	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
EM-6630RS	OPEN	1/2 - 1/3	115	6.40	600/1200	11.75"	1/2" x 5.50"	REV.
EM-6640RS	OPEN	3/4	115	9.30	600/1200	12.25"	1/2" x 5.50"	REV.
EM-6650RS	OPEN	1	115	10.60	600/1200	12.75"	1/2" x 5.50"	REV.
EM-6631RS	OPEN	1/2 - 1/3	208 - 230	4.60 / 4.30	600/1200	11.75"	1/2" x 5.50"	REV.
EM-6641RS	OPEN	3/4	208 - 230	6.30 / 6.10	600/1200	11.25"	1/2" x 5.50"	REV.
EM-6651RS	OPEN	1	208 - 230	6.40 / 6.60	600/1200	12.75"	1/2" x 5.50"	REV.

† All marks shown within this document are properties of their respective owners.

MULTI-HP RATED MOTORS

Features:

- P.S.C. Design
- Energy Efficient
- Resilient Rings
- 40°C Ambient
- Reversible Rotation
- Open Construction
- Class 'B' Insulation
- Extended Thru Bolts
- Rheem Mounting Holes in Shell
- Sleeve and Ball Bearings



All Models

48 Frame - Four Speed

OMNIDRIVE®

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Capacitor
SS3463 *	OPEN	1/2	115	7.00	1075/4	1/2" x 5.00"	10/370, 7.5/370
SS3464 *	OPEN	1/2	208-230	3.90	1075/4	1/2" x 5.00"	5/370
SS3466 *	OPEN	3/4	115	9.10	1075/4	1/2" x 5.00"	5/370
SS3467 *	OPEN	3/4	208-230	3.90	1075/4	1/2" x 5.00"	5/370

Cross Reference

Century	Emerson	Genteq	Marathon	Fasco	Rotom
FDL6001A	5460	3463	X077	D2835	R43600
FD6000A	5461	3464	X073	D833	R43601
FDL6002A	5470	3466	X074	D2832	R43602
FD6001A	5471	3467	X075	D2833	R43603

Features:

- Resilient Rings Included
- Permanent Split Capacitor Design
- Reversing Plug
- Extended Thru Bolts
- Thermally Protected
- 40°C Ambient Rating
- Long Life Self-Aligning Sleeve Bearings



EM-1390 - EM-1391



All OmniDrive Models



EM-8906 - EM-8907
5BD1076 - 5BD1106

42 Frame - Three Speed



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
EM-1390 *	OPEN	1/4	115	2.80	1075/3	1/2"x4.00"	REV.	D150
EM-1391 *	OPEN	1/4	208-230	1.50	1075/3	1/2"x4.00"	REV.	D151

48 Frame - Three Speed



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS3583 *	OPEN	1/4	115	4.20	1075/3	1/2"x4-1/2"	REV.	DD-3583
SS3584 *	OPEN	1/4	208-230	2.00	1075/3	1/2"x4-1/2"	REV.	DD-3584
SS1314 *	OPEN	1/3	115	6.00	1075/4	1/2"x5-1/8"	CCWLE	DD-1314, F1314D
SS3585 *	OPEN	1/3	115	5.50	1075/3	1/2"x4-1/2"	REV.	D-3585
SS3586 *	OPEN	1/3	208-230	2.80	1075/3	1/2"x4-1/2"	REV.	DD-3586
SS3587 *	OPEN	1/2	115	7.50	1075/3	1/2"x4-1/2"	REV.	DD-3587
SS3588 *	OPEN	1/2	208-230	3.60	1075/3	1/2"x4-1/2"	REV.	DD-3588
SS3589 *	OPEN	3/4	115	10.20	1075/3	1/2"x4-1/2"	REV.	DD-3589
SS3590 *	OPEN	3/4	208-230	5.50	1075/3	1/2"x4-1/2"	REV.	DD-3590
EM-8906 •*	OPEN	1	115	12.30	1075/3	1/2"x6-7/16"	REV.	R42812
EM-8907 •*	OPEN	1	208-230	5.10	1075/3	1/2"x6-7/16"	REV.	R42023
5BD1076 •*	OPEN	3/4	575	2.30	1075/2	1/2"x5.00"	REV.	HQ1095096
5BD1106 •*	OPEN	1	575	2.40	1075/2	1/2"x5.00"	REV.	F1575DD

Features:

- Fits 9" & 10" Bolt Circle Diameter
- Permanent Split Capacitor Design
- Reversing Plug
- Thermally Protected
- 40°C Ambient Rating
- Long Life Self-Aligning Sleeve Bearings



All Models

48 Frame - Four Speed



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS752*	OPEN	1/4	115	3.60	1075/4	1/2"x6.00"	REV.	DD-034
SS753*	OPEN	1/3	115	4.80	1075/4	1/2"x6.00"	REV.	DD-035
SS754*	OPEN	1/2	115	8.20	1075/4	1/2"x6.00"	REV.	DD-036
SS753B•*+	OPEN	1/3	115	4.80	1075/4	1/2"x6.00"	REV.	
SS754B•*+	OPEN	1/2	115	8.20	1075/4	1/2"x6.00"	REV.	
SS972 *	OPEN	1/4	208-230	1.80	1075/4	1/2"x6.00"	REV.	DD-044
SS973 *	OPEN	1/3	208-230	2.30	1075/4	1/2"x6.00"	REV.	DD-045
SS974*	OPEN	1/2	208-230	3.80	1075/4	1/2"x6.00"	REV.	DD-046

(•) Ball Bearing (*) P.S.C. Design (+) Capacitor Included




Ultimate Truck Stock Motor™

Features:

- High Efficiency P.S.C. Design
- Extended Mounting Studs
- Designed for Use With 370V Capacitors
- Class 'B' Insulation
- 36" Leads
- Includes Side Shell Holes For Rheem Units
- Continuous Duty, Air Over
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- 2.5" Diameter Hub Rings Included
- Sleeve and Ball Bearings



All Models



48 Frame - Four Speed



Stock #	Encl.	HP	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
EM-5469 *	OPEN	1/3	208-230	2.40	825/4	6.74"	1/2" x 2.20"	REV.
EM-5460 *	OPEN	1/2	115	7.30	1075/4	9.80"	1/2" x 5.00"	REV.
EM-5461 *	OPEN	1/2	208-230	3.60	1075/4	9.80"	1/2" x 5.00"	REV.
EM-5470 ●*	OPEN	3/4	115	8.10	1075/4	11.60"	1/2" x 5.00"	REV.
EM-5471 ●*	OPEN	3/4	208-230	4.10	1075/4	11.60"	1/2" x 5.00"	REV.

Cross Reference


	Rotom	Genteq	A.O. Smith	Marathon	Fasco
EM-5469	N/A	N/A	N/A	N/A	N/A
EM-5460	R6-R43600	3463	FDL6001A	X077	D2835
EM-5461	R6-R43601	3464	FD6000A	X073	D833
EM-5470	R6-R43602	3466	FDL6002A	X074	D2832
EM-5471	R6-R43603	3467	FD6001A	X075	D2833



RESCUE EcoTech®

Features:

- Electronically Controlled Brushless Permanent Magnet Motor
- Up to 82% Efficiency
- Saves 25% of the Watts in A/C or Heating
- 75% Watt Reduction in Circulation Mode
- Easy Voltage Change from 230V to 115V
- Electronically Protected Motor
- Continuous Duty, Air Over
- No Capacitor Required
- 6000V Surge Protection
- Reversible Rotation
- Class 'B' Insulation
- 36" Leads
- 40°C Ambient
- Ball Bearings



48 Frame - Five Speed



Stock #	Incl.	HP Range	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
EM-5522ET•	OPEN	1/3 - 1/5	115 / 230	4.02 / 2.70	1075/5	9.75"	1/2" x 4.50"	REV.
EM-5532ET•	OPEN	1/2 - 1/4	115 / 230	6.20 / 3.90	1075/5	9.75"	1/2" x 4.50"	REV.
EM-5542ET•	OPEN	3/4 - 1/3	115 / 230	8.50 / 5.20	1075/5	10.75"	1/2" x 4.50"	REV.
EM-5552ET•	OPEN	1 - 1/2	115 / 230	11.50 / 6.90	1075/5	11.25"	1/2" x 4.50"	REV.

Cross Reference

	Rotom	Genteq	Mars	A.O. Smith
EM-5522ET	N/A	6103E*	N/A	N/A
EM-5532ET	R6-R75531 R6-R755301	6105E*	06005	CSL1056 CS1056
EM-5542ET	N/A	6107E*	N/A	N/A
EM-5552ET	R6-R75551 R6-R755501	6110E*	06010	CSL1106 CS1106


(*) 115 Volt Only

- **Fits a Wide Variety of Applications** - The fully reversible motor comes in a range of horsepower sizes to fit your market and is dual voltage so you can provide an indoor blower solution to all your customers.
- **Quiet, Efficient Circulation Speed** - With a low 600 RPM circulation speed, your customers can cycle air continuously without the noise, draft or electricity cost of a PSC motor. Often using less energy than a 100 watt bulb. Up to 75% watts savings are typical.
 - **Active Airflow Management** - The advanced motor control reacts to change in static pressure, helping to maintain airflow as vents are closed or the filter becomes dirty.
 - **Very Energy Efficient** - The RESCUE EcoTech motor is up to 25% more electrically efficient at high speed compared to a standard blower motor. 75% watt reduction in circulation mode.



Features:

- Single Phase P.S.C.
- Thermally Protected
- Reversible Rotation
- 36" Leads
- Continuous Duty, Air Over
- Extended Mounting Studs
- High Efficiency Design
- Ball Bearings



60°C Ambient



All Models

42 Frame



Stock #	Encl.	HP Range	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
9722 ●*	T.E.	1/8 - 1/12	208-230	0.90	1075	7.50"	1/2" x 3.00"	REV.
9723 ●*	T.E.	1/4 - 1/6	208-230	2.00	1075	7.50"	1/2" x 3.00"	REV.
9724 ●*	T.E.	1/4 - 1/6	208-230	1.60	1625	7.50"	1/2" x 3.00"	REV.

Motor Mount Brackets & Capacitors



Accessories

Stock #	Description
1330A	Rain Shield for 1/2" Shaft
1383A	Rain Shield for 5/8" Shaft
EM-43	5" (42 Frame) 9" & 10" B.C.D. 3 Lugs
EM-44	5-5/8" (48 Frame) 9" & 10" B.C.D. 3 Lugs
EM-39	5-5/8" (48 Frame) 9" & 10" B.C.D. 4 Lugs
EM-17	Heavy Duty 5-5/8" (48 Frame) 10" B.C.D. 3 Lugs
EM-23	Heavy Duty 5-5/8" (48 Frame) 11" B.C.D. 3 Lugs
EM-24	Heavy Duty 5-5/8" (48 Frame) 15" B.C.D. 4 Lugs
EM-29	Heavy Duty 5-5/8" (48 Frame) 16" B.C.D. 4 Lugs
1482A	Capacitor Mounting Bracket & Rubber Cover
POC5-1	5mfd / 370V. Oval Case
POC7.5-1	7.5mfd / 370V. Oval Case
POC10-1	10mfd / 370V. Oval Case
POC15-1	15mfd / 370V. Oval Case



Ultimate Truck Stock Motor™


Features:

- High Efficiency P.S.C. Design
- EZ-FIT® Mounting System to Cover 4.3", 4.4" or 4.6" Bolt Circle Mounts
- High 70°C (158°F) Ambient Design
- Automatic Reset Thermal Overload Protector
- Designed for Use with 370V Capacitors
- Special Treated Rotor For Corrosion Protection
- Totally Enclosed, Air Over (TEAO)
- Continuous Duty, Air Over
- Extended Mounting Studs
- Reversible Rotation
- 36" Leads
- Ball Bearings

70°C Ambient



All Models



42 Frame



Stock #	Encl.	HP Range	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
EM-5440H ●*	T.E.	1/8 - 1/12	208-230	0.80	1075	8.00"	1/2" x 3.00"	REV.
EM-5441H ●*	T.E.	1/4 - 1/6	208-230	1.50	1075	8.50"	1/2" x 3.00"	REV.
EM-5442H ●*	T.E.	1/4 - 1/6	208-230	1.60	1625	8.50"	1/2" x 3.00"	REV.

Cross Reference

	Rotom *	Genteq *	A.O. Smith *	Fasco *
EM-5440H	M4-R2722	2S005, 2251	9722	G2243, G2248, G2249
EM-5441H	M4-R2723	2S003, 2250	9723	G2247, G2246, G2244, G2245
EM-5442H	M4-R2724	N/A	9724	N/A

(*) These motors are rated 60°C Ambient




EZ-FIT® Motor Mounting Bracket
Assembled out of the box to use as a clam shell replacement. Easily adapts to a 4.4" or 4.6" bolt circle for other applications



**Clam Shell
4.3" Bolt Circle**



**3 Pc
4.4" Bolt Circle**





**3 Pc
4.6" Bolt Circle**

(●) Ball Bearing (*) P.S.C. Design



Features:

- Single Phase P.S.C.
- Totally Enclosed, Air Over
- Reversible Rotation
- Automatic Overload
- Ball Bearings



208-230V - 825 RPM

OMNIDRIVE®



Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
SS3403 ●	T.E.A.O	1/6	208-230	1.10	825	4.11"	1/2" x 6.00"	REV.	CF-816, 3203
SS3404 ●	T.E.A.O	1/4	208-230	1.50	825	4.61"	1/2" x 6.00"	REV.	CF-814, 3204
SS3405 ●	T.E.A.O	1/3	208-230	1.80	825	5.11"	1/2" x 6.00"	REV.	CF-813, 3205
SS3746 ●	T.E.A.O	1/2	208-230	2.70	825	5.61"	1/2" x 6.00"	REV.	CF-812, 3747HS



208-230V - 1075 RPM

Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
SS3727 ●	T.E.A.O	1/6	208-230	1.10	1075	3.86"	1/2" x 6.00"	REV.	CF-3726, 3727
SS3728 ●	T.E.A.O	1/4	208-230	2.00	1075	4.11"	1/2" x 6.00"	REV.	CF-3732, 3732
SS3729 ●	T.E.A.O	1/3	208-230	2.50	1075	4.61"	1/2" x 6.00"	REV.	CF-3733, 3733
SS3730 ●	T.E.A.O	1/2	208-230	3.40	1075	5.11"	1/2" x 6.00"	REV.	CF-3734, 3734
SS3731 ●	T.E.A.O	3/4	208-230	5.30	1075	5.36"	1/2" x 6.00"	REV.	CF-3735, 3735

460V - 825 RPM

Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
EM-1880 ●	T.E.A.O	1/4	460	1.00	825	5.10"	1/2" x 6.00"	REV.	---
EM-1881 ●	T.E.A.O	1/3	460	1.00	825	5.60"	1/2" x 6.00"	REV.	3209

575V - 825 RPM

Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
SS3756 ●	T.E.A.O	1/4	575	0.70	825	4.81"	1/2" x 5.00"	REV.	---
SS3757 ●	T.E.A.O	1/3	575	1.10	825	5.31"	1/2" x 5.00"	REV.	---

575V - 1075 RPM


Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
5FE1036S ●	T.E.A.O	1/3	575	0.80	1100	5.36"	1/2" x 6.50"	REV.	R42604
5FE1056S ●	T.E.A.O	1/2	575	1.20	1100	5.61"	1/2" x 6.50"	REV.	R42606
5FE1076S ●	T.E.A.O	3/4	575	1.90	1075	6.11"	1/2" x 6.50"	REV.	R42607

575V - 1625 RPM

Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
SS3762 ●	T.E.A.O	1/2	575	1.00	1625	5.30"	1/2" x 6.50"	REV.	R42605, D2750

Features:

- Single Phase P.S.C.
- Totally Enclosed, Air Over
- Reversible Rotation
- Automatic Overload
- Ball Bearings



70°C Ambient



208-230V - 825 RPM

OMNIDRIVE®



Formerly Emerson Motors

Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
SS7403 ●	T.E.A.O	1/6	208-230	1.10	825	4.11"	1/2" x 6.00"	REV.	3203HS
SS7404 ●	T.E.A.O	1/4	208-230	1.40	825	4.68"	1/2" x 6.00"	REV.	3204HS
SS7405 ●	T.E.A.O	1/3	208-230	1.80	825	5.11"	1/2" x 6.00"	REV.	3205HS
SS7746 ●	T.E.A.O	1/2	208-230	2.50	825	5.61"	1/2" x 6.00"	REV.	3747HS



Formerly A.O. Smith Electrical Products Company

208-230V - 1075 RPM

Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
SS7727 ●	T.E.A.O	1/6	208-230	1.10	1075	3.86"	1/2" x 6.00"	REV.	3726HS
SS7728 ●	T.E.A.O	1/4	208-230	2.00	1075	4.11"	1/2" x 6.00"	REV.	3732HS
SS7729 ●	T.E.A.O	1/3	208-230	2.50	1075	4.61"	1/2" x 6.00"	REV.	3733HS
SS7730 ●	T.E.A.O	1/2	208-230	3.50	1075	5.11"	1/2" x 6.00"	REV.	3734HS
SS7731 ●	T.E.A.O	3/4	208-230	5.30	1075	5.36"	1/2" x 6.00"	REV.	3735HS

460V - 1075 RPM

Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
SS7736 ●	T.E.A.O	1/4	460	1.00	1075	4.74"	1/2" x 6.00"	REV.	3736HS
SS7737 ●	T.E.A.O	1/3	460	1.30	1075	5.24"	1/2" x 6.00"	REV.	3737HS
SS7738 ●	T.E.A.O	1/2	460	1.50	1075	5.61"	1/2" x 6.00"	REV.	3738HS

575V - 1075 RPM


Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation	Replaces
SS3758 ●	T.E.A.O	1/4	575	0.60	1075	4.31"	1/2" x 5.00"	REV.	---
SS3759 ●	T.E.A.O	1/3	575	0.70	1075	5.31"	1/2" x 5.00"	REV.	---
SS3760 ●	T.E.A.O	1/2	575	0.90	1075	5.56"	1/2" x 5.00"	REV.	---
SS3761 ●	T.E.A.O	3/4	575	1.60	1075	7.31"	1/2" x 5.00"	REV.	---



Ultimate Truck Stock Motor™

Features:

- High Efficiency P.S.C. Design
- High 70°C (158°F) Ambient Design
- Automatic Reset Thermal Overload Protector
- Designed for Use With 370V Capacitors
- Special Treated Rotor For Corrosion Protection
- Includes Lead End Mounting Holes For Rheem or Trane Units
- Class 'F' Insulation
- Extended Mounting Studs
- Flat Lead End for Shaft Down Applications
- Reversible Rotation
- Continuous Duty, Air Over
- 48" Leads with Flag Terminals
- Ball Bearings



70°C Ambient



All Models

48 Frame - Two Speed



Stock #	HP Range	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
EM-5464H ●*	1/3 - 1/6	208-230	1.90 - 1.00	825/2	10.30"	1/2" x 5.00"	REV.
EM-5462H ●*	1/3 - 1/6	208-230	2.60 - 1.80	1075/2	9.60"	1/2" x 5.00"	REV.
EM-5465H ●*	1/2 - 1/5	208-230	3.00 - 1.30	1075/2	10.30"	1/2" x 5.00"	REV.
EM-5482H ●*	3/4 - 1/4	208-230	4.00 - 1.40	1075/2	11.87"	1/2" x 5.00"	REV.
EM-5480H ●*	1/2 - 1/6	460	1.30 - 0.50	1075/2	11.10"	1/2" x 5.00"	REV.
EM-5481H ●*	3/4 - 1/4	460	2.20 - 0.70	1075/2	11.85"	1/2" x 5.00"	REV.

Cross Reference

	Rotom	Genteq	Century
EM-5464H	M2-R22601	3457HS, 3459HS	FE6001F
EM-5462H	M2-R22600	3456HS, 3458HS	FE6000F
EM-5465H	M2-R22602	3460HS	FE6002F
EM-5482H	M2-R22604	N/A	FE6003F
EM-5480H	N/A	N/A	N/A
EM-5481H	N/A	N/A	N/A

Features:

- Open Opposite Shaft-End & Totally Enclosed
- Single Phase P.S.C. & Three Phase
- Round Body & Rigid Base
- Reversible Rotation
- Auto Protection
- Ball Bearings



C770 - C081 - C771 - 181574



H564 - H977- H567 - H961
H667 - H962 - H767 - H963



UEH962 - UEH686 - UEH699 - UEX526



RMT0062



MA1074



181651

56 Frame - Single Phase



Formerly A.O. Smith Electrical Products Company



Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
C770 ●*	O.O.S.E.	1	200-230 / 460-1Ø	4.80 / 2.40	1075	5/8" x 6.00"	REV.	S1514
C081 ●*	O.O.S.E.	1	575-1Ø	2.20	1075	5/8" x 6.00"	REV.	S1516
C771 ●*	O.O.S.E.	1.5	200-230 / 460-1Ø	6.60 / 3.30	1075	5/8" x 6.00"	REV.	S1518
181574 ●*	O.O.S.E.	1.5	575-1Ø	2.70	1075	5/8" x 6.00"	REV.	S1520

56 Frame - Three Phase




Formerly Emerson Motors

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
H564 ●	O.O.S.E.	1/2	200-230 / 460-3Ø	2.8-2.6 / 1.30	1140	5/8" x 6.00"	REV.	T2532
H977 ●	T.E.	1/2	575-3Ø	0.80	1140	5/8" x 3-3/8"	REV.	AICH977
H567 ●	O.O.S.E.	3/4	200-230 / 460-3Ø	2.8-3.0 / 1.50	1140	5/8" x 6.00"	REV.	T2534
H961 ●	O.O.S.E.	3/4	575-3Ø	1.25	1140	5/8" x 6.00"	REV.	T2535
H667 ●	O.O.S.E.	1	200-230 / 460-3Ø	5.3-5.2 / 2.60	1140	5/8" x 6.00"	REV.	T2538
H671 ●	O.O.S.E.	1	575-3Ø	2.00	1140	5/8" x 6.00"	REV.	T2540
UEH686 ●	O.O.S.E.	1	208-230 / 460-3Ø	5.0 / 2.5	850	5/8" x 6.00"	REV.	T2537
H686 ●	O.O.S.E.	1	200-230 / 460-3Ø	4.4-4.0 / 2.00	850	5/8" x 5.00"	REV.	T2537
UEH962 ●	O.O.S.E.	1	575-3Ø	2.10	850	5/8" x 6.00"	REV.	T2539
H962 ●	O.O.S.E.	1	575-3Ø	1.60	850	5/8" x 3-1/4"	REV.	T2539
H767 ●	O.O.S.E.	1.5	200-230 / 460-3Ø	5.8-6.0 / 3.00	1140	5/8" x 6.00"	REV.	T2542
H963 ●	O.O.S.E.	1.5	575-3Ø	2.30	1140	5/8" x 6.00"	REV.	T2543
UEH699 ●	O.O.S.E.	2	208-230 / 460-3Ø	7.8 / 3.90	1140	5/8" x 6.00"	REV.	T2544
H978 ●	O.O.S.E.	SPL	208-230 / 460/575-3Ø	5.5 / 3.4 / 2.80	1140	5/8" x 3-1/2"	REV.	HD52AK652
RMT0062 ●	O.O.S.E.	1.5	575-3Ø	2.50	860	5/8" x 2-1/2"	REV.	RMT0062
MA1074 ●	T.E.	2	575-3Ø	3.10	1140	5/8" x 3.00"	REV.	MA1074
UEX526 ●	O.O.S.E.	2	575-3Ø	2.80	1140	5/8" x 6.00"	REV.	T2536, X526
181651 ●	T.E.	2	575-3Ø	2.70	1140	5/8" x 2-1/2"	REV.	---

● Ball Bearing (*) P.S.C. Design

Features:

- Open Opposite Shaft-End
- Inverter Duty
- Class 'F' Insulation
- Automatic Overload
- Energy Efficient
- Reversible Rotation
- Ball Bearings
- Removable Bolt-on Base



70°C Ambient



56 Frame - Three Phase - 208-230/460V



Stock #	Encl.	HP	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
H1055A ●	O.O.S.E.	1/2	208-230/460	2.8-2.6 / 1.3	1140	16.09"	5/8" x 6.00"	REV.
H1056A ●	O.O.S.E.	3/4	208-230/460	2.8-3.0 / 1.5	1140	16.20"	5/8" x 6.00"	REV.
H1050A ●	O.O.S.E.	1	208-230/460	4.0-4.4 / 2.2	1140	16.30"	5/8" x 6.00"	REV.
H1051A ●	O.O.S.E.	1-1/2	208-230/460	5.8-5.8 / 2.9	1140	17.32"	5/8" x 6.00"	REV.
H1052A ●	O.O.S.E.	2	208-230/460	7.0-7.4 / 3.7	1140	18.32"	5/8" x 6.00"	REV.
H1053A ●	O.O.S.E.	1	208-230/460	5.0-5.2 / 2.6	850	18.32"	5/8" x 6.00"	REV.
H1054A ●	O.O.S.E.	1-1/2	208-230/460	5.0-5.2 / 2.6	850	18.77"	5/8" x 6.00"	REV.

56 Frame - Three Phase - 575V

Stock #	Encl.	HP	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
5H1050A ●	O.O.S.E.	1	575	2.00	1140	16.30"	5/8" x 6.00"	REV.
5H1051A ●	O.O.S.E.	1-1/2	575	2.40	1140	17.30"	5/8" x 6.00"	REV.
5H1052A ●	O.O.S.E.	2	575	3.00	1140	18.30"	5/8" x 6.00"	REV.
5H1053A ●	O.O.S.E.	1	575	1.80	850	18.30"	5/8" x 6.00"	REV.
5H1054A ●	O.O.S.E.	1-1/2	575	3.00	850	18.78"	5/8" x 6.00"	REV.



Blanchard-Ness

Stock #	Incl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS605	SKEL	---	120	1.00	2800	3/16" x 1-3/4"	CCWSE	AIC605
572A	OPEN	1/20	115	1.90	1550	5/16" x 3.00"	CWSE	D1124
573A	OPEN	1/15	208-230	1.30	1550	5/16" x 3.00"	CWSE	D1126
SS358	OPEN	1/20	115	2.00	1550	5/16" x 3.00"	CWSE	AIC1052
SS359	OPEN	1/20	208-230	1.10	1430	5/16" x 3.00"	CWSE	AIC1053
SS302	OPEN	1/100	240	0.30	1400	1/4" x 1.50"	CCWSE	E1004
SS326	OPEN	1/85	115	0.50	1550	1/4" x 1.45"	CCWSE	79101, E1001 E1002, E1003
EM-9662 ●*	OPEN	1/20	115	0.85	1550	5/16" x 3.00"	REV.	MA1009
EM-9656 ●*	OPEN	1/15	208-230	0.48	1550	5/16" x 3.00"	REV.	MA1010
UEH977	O.O.S.E.	1/2	575	0.85	1140	5/8" x 3.30"	REV.	AICH977, T2533, T2529
SS3729 ●*	T.E.	1/3	208-230	2.50	1075	1/2" x 6.00"	REV.	E1022, E1025
SS3730 ●*	T.E.	1/2	208-230	3.40	1075	1/2" x 6.00"	REV.	E1064
H564 ●	O.O.S.E.	1/2	200-230/460	2.8-2.6 / 1.30	1140	5/8" x 6.00"	REV.	E1020, E1066
H977 ●	T.E.	1/2	575-3Ø	0.80	1140	5/8" x 3-3/8"	REV.	AICH977
H686	O.O.S.E.	1	200-230/460-3Ø	4.4-4.0 / 2.00	850	5/8" x 5.00"	REV.	T2537
UEH686 ●	O.O.S.E.	1	208-230/460-3Ø	5.0 / 2.50	850	5/8" x 5.00"	REV.	X507
H962 ●	O.O.S.E.	1	575-3Ø	1.60	850	5/8" x 3-1/4"	REV.	X527
UEH962 ●	O.O.S.E.	1	575-3Ø	2.10	850	5/8" x 6.00"	REV.	X527
UEH699 ●	O.O.S.E.	2	208-230/460-3Ø	7.8 / 3.90	1140	5/8" x 6.00"	REV.	X509
UEX526 ●	O.O.S.E.	2	575-3Ø	2.80	1140	5/8" x 6.00"	REV.	X526



Cancoil Thermal

Stock #	Incl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
EM-9662 ●*	OPEN	1/20	115	0.85	1550	5/16" x 3.00"	REV.	MA1009
EM-9656 ●*	OPEN	1/15	208-230	0.48	1550	5/16" x 3.00"	REV.	MA1010
H977 ●	T.E.	1/2	575-3Ø	0.80	1140	5/8" x 3-3/8"	REV.	AICH977
181651 ●	T.E.	2	575-3Ø	2.70	1140	5/8" x 2-1/2"	REV.	MA1003
MA1074 ●	T.E.	2	575-3Ø	3.10	1140	5/8" x 3.00"	REV.	CAN2575
H698 ●	T.E.	2	208-230/460	6.8-6.2 / 3.10	1140	5/8" x 6.00"	REV.	MA1075

(●) Ball Bearing (*) P.S.C. Design



Carrier

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS1506 ●*	SEMI-ENCL	1/2	575	1.80	1075	1/2" x 1-9/16"	CCWLE	CCFM12575, HC43VE575
OCA1056 ●*	SEMI-ENCL	1/2	200-230	4.60 / 2.30	1075	1/2" x 1-9/16"	REV.	3288, HC43VE200B
5OCA3056 ●	SEMI-ENCL	1/2	575-3Ø	1.00	1140	1/2" x 2-1/2"	REV.	HD44ML461, P48J6A2
5BD1106 ●*	OPEN	1	575	2.40	1075/2	1/2" x 5.00"	REV.	F1575DD, 50HJ900575
H953V1 ●	OPEN	2	575-3Ø	2.40	1800	7/8" x 2.30"	REV.	F21853, HD52GA875
UEH953 ●	OPEN	2	575-3Ø	2.70	1725	7/8" x 2-1/4"	REV.	F21853, HD52GA875
H955L ●	OPEN	3	575-3Ø	3.60	1800	7/8" x 2.30"	REV.	F31853, HD58DL575
UEH955 ●	OPEN	3	575-3Ø	3.40	1800	7/8" x 2.30"	REV.	F31853, HD58DL575
181574 ●	O.O.S.E.	1.5	575	2.70	1075	5/8" x 6.00"	REV.	CCFM1575, HC51TE575
H978 ●	O.O.S.E.	SPL	208-230/460/575-3Ø	5.5/3.4/2.8	1140	5/8" x 3-5/8"	REV.	HD52AK652
H979L ●	OPEN	5	208-230/460-3Ø	15.00 / 7.40	1725	7/8" x 2-5/16"	REV.	HD60FK652
H980L ●	OPEN	3	208-230/460-3Ø	10.60 / 4.80	1725	7/8" x 2-5/16"	REV.	HD60FK651
HD60FE575 ●	OPEN	5	575-3Ø	5.60	1725	7/8" x 3-1/4"	REV.	HD60FE575



Copeland


Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
254	OPEN	35W	115	1.40	1500	Hubless	CWLE	R3511, 050-0227-01
256	O.O.S.E	35W	230	0.70	1500	Hubless	CWLE	R3512, 050-0227-02
260	OPEN	50W	230	0.85	1500	3/8" x 1-1/2"	CWLE	R5012, 050-0017-01
174A *	OPEN	1/6	208-230	1.00	1625	1/2" x 2-1/2"	REV.	R3051
OCP0251 *	OPEN	1/6	230	1.50	1625	1/2" x 2-1/2"	CCWSE	050-0251-00
OCP0250 *	OPEN	1/4	230	1.50	1625	1/2" x 2-1/2"	CWLE	050-0250-00
OCP1024 ●*	OPEN	1/4	208-230	1.50	1625	1/2" x 3.00"	CWLE	R3047, 050-0107-01
EM-1265 *	OPEN	1/6	460	0.55	1550	1/2" x 3-1/16"	CWLE	050-0265-01 050-
EM-1275 *	OPEN	1/4	575	0.70	1625	1/2" x 3.00"	CWLE	0250-02 050-0266-02



SS9428

Dunham Bush

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS9428	OPEN	1	575	1.70	1100	1/2" x 2-3/4"	REV.	HM3T007, HM3T010



160A

OHR1106

Hill

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
160A *	OPEN	1/3	208-230	3.00	1625	1/2" x 4.00"	REV.	R3001, PP3955B
OHR1106 ●*	SEMI-ENCL	1	208-230	7.10 / 6.40	1075	1/2" x 3-3/4"	REV.	R3067, PP19162G



SS605



572A - 573A



EM-9662 - EM-9656



SS9721



SS3729 - SS3730

EM-4941

Heatcraft (Bohn/Larkin)

Stock #	Encl.	HP	Volts	Amps	RPM	Shaft	Rotation	Replaces
SS605	SKEL	---	120	1.00	2800	3/16" x 1-3/4"	CCWSE	AIC605
572A	OPEN	1/20	115	1.90	1550	5/16" x 3.00"	CWSE	D1124
EM-9662 ●*	OPEN	1/20	115	0.85	1550	5/16" x 3.00"	REV.	5001L, 5008S, 5004L 5034L, 5034LS, 5008SS
573A	OPEN	1/15	208-230	1.30	1550	5/16" x 3.00"	CWSE	D1126
EM-9656 ●*	OPEN	1/15	208-230	0.48	1550	5/16" x 3.00"	REV.	7190-0442, 25309101 5008T, 5034M, 5034MS
SS9721 ●*	OPEN	1/12	115/208-230	1.10/0.60	1550	5/16" x 3.15"	REV.	R90721, 253-9101
SS9729 ●*	T.E.	1/3	208-230	2.50	1075	1/2" x 6.00"	REV.	CF-3733
SS9730 ●*	T.E.	1/2	208-230	3.40	1075	1/2" x 6.00"	REV.	CF-3734
EM-4941 ●*	T.E.	1/2	208-230/460	2.80/1.50	1100	1/2" x 4-1/2"	REV.	---

● Ball Bearing (*) P.S.C. Design



Hussmann

Stock #	Encl.	HP	Volt	Amps	RPM	Shaft	Rotation	Replaces
OHS1004 *	OPEN	1/8	230	1.00	1550	1/2" x 2.00"	CWLE	3011
174A *	OPEN	1/6	208-230	1.00	1625	1/2" x 2-1/2"	REV.	3057
OHS1016 *	OPEN	1/5	230	1.60	1075	1/2" x 3.00"	CWLE	3009
OHS10206 ●*	OPEN	1/5	208-230	1.30	1075	1/2" x 3.00"	CWLE	3008/3012
OHS9983 ●*	OPEN	1/2	208-230	2.70	1725	1/2" x 3-1/2"	CWLE	R3051, 259983
F062P ●	OPEN	1/20	600	0.42	1550	1/2" x 2-1/2"	CWSE	206578, HHCFM DA2F062, DA2F091
SS34201 ●*	OPEN	1/2	575	0.50	1075	1/2" x 3.30"	CCWSE	204201, R34201
J055U ●*	T.E.	1/6	575	0.80	1675	1/2" x 3.20"	REV.	77238, 1042140 R30575, FM001
H667 ●	O.O.S.E	1	200-230/460-3Ø	5.3-5.2/2.6	1140	5/8" x 6.00"	REV.	T2540
H671 ●	O.O.S.E	1	575-3Ø	2.00	1140	5/8" x 6.00"	REV.	T2538



Keeprite

Stock #	Encl.	HP	Volt	Amps	RPM	Shaft	Rotation	Replaces
SS370 ●*	OPEN	1/20	115	0.80	1550	5/16" x 2.80"	CCWSE	R370
SS371 ●*	OPEN	1/20	230	0.30	1550	5/16" x 2.80"	CCWSE	R371
SS2269	OPEN	1/15	115	2.70	1050	1/2" x 2.75"	CWSE	160269, R2269
SS2657	OPEN	1/15	230	1.20	1550	3/8" x 2.44"	CCWSE	81335, R2657
SS2658	OPEN	1/15	115	2.30	1550	3/8" x 2.44"	CCWSE	81356, R2658
FE1026 ●*	T.E.A.O.	1/4	208-230	1.80	1075/2	1/2" x 6.00"	REV.	AICF171672
G004U ●	T.E.	1/4	575-3Ø	0.46	1100	5/8" x 2.93"	REV.	171065, R31065
5BD1076 ●*	OPEN	3/4	575-1Ø	2.30	1075/2	1/2" x 5.00"	REV.	F34575DD, HQ1095096
176826 ●	OPEN	1.25	208-230-3Ø	4.70-5.00	1140	5/8" x 3-1/4"	REV.	1043297-001, T1826
173946 ●	OPEN	1.25	575-3Ø	2.00	1140	5/8" x 3-1/4"	REV.	1043299-01, T1946
187289 ●	OPEN	1 SPL	575-3Ø	2.30	850	5/8" x 3-1/4"	REV.	1062968-001



9627 - 9628



EM-9662 - EM-9656



OKR1096



OKR1503

Krack

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
9627	T.E.	1/25	115	1.30	1550	5/16" x 1-3/4"	CWSE	11528, JAZP216
9628	T.E.	1/20	200-230	0.90	1550	5/16" x 1-1/2"	CWSE	11529, JA2P217 JA2S149
EM-9662 ●*	OPEN	1/20	115	0.85	1550	5/16" x 3.00"	REV.	9633, E206447
EM-9656 ●*	OPEN	1/15	208-230	0.48	1550	5/16" x 3.00"	REV.	9634, E206448
OKR1096 ●	T.E.A.O.	1/2	208-230/460-3Ø	2.0-1.9/0.95	1140	5/8" x 2.00"	REV.	150372, 11096
OKR1503 ●	O.O.S.E.	1	200-230/460-3Ø	4.4-4.0/2.00	850	5/8" x 3-1/4"	REV.	151437, 11503



EM-1268



SS1314



9405A



9406A



LX7930 - 5BD1106



H671



H953V1



UEH953

Lennox

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
EM-1268 *	OPEN	1/5	115	3.50	1075/4	1/2" x 3.50"	REV.	P-8-9662
SS1314 *	OPEN	1/3	115	6.00	1075/4	1/2" x 5-1/8"	CCWLE	DD-1314, F1314D
9405A ●*	OPEN	3/4	115	9.70	1075/5	1/2" x 3-1/8"	CCWLE	45H3301, 28F01
9406A ●*	OPEN	3/4	208-230	6.60	1075/3	6-1/2" x 5/8" x 5-1/4"	CCWLE	31C8201
LX7930 *	OPEN	3/4	460	2.30	1075/3	1/2" x 2.50"	CWSE	43G5201
5BD1106 ●*	OPEN	1	575	2.40	1075/2	1/2" x 5.00"	REV.	F34575DD, 88C7601
H671 ●	O.O.S.E.	1	575-3Ø	2.00	1140	5/8" x 6.00"	REV.	98G6501
H953V1 ●	OPEN	2	575-3Ø	2.40	1800	7/8" x 2.30"	REV.	32657/F21853
UEH953 ●	OPEN	2	575-3Ø	2.70	1725	7/8" x 2-1/4"	REV.	32657/F21853



C663



SS2531 - SS2535

Liebert

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
C663	O.O.S.E.	3/4	208-230/460	4.80-4.20/2.10	1100	5/8" x 4.00"	CCWLE	B-0950
SS2531	O.O.S.E.	1	208-230/460	4.20/2.10	1140	5/8" x 6.00"	REV.	R2531
SS2535	O.O.S.E.	1	575	1.50	1140	5/8" x 3.20"	REV.	R2535



EM-9662 - EM-9656



SS368 - SS369



RMT0004 - RMT0005



RMT0062



MA1074

Ref Plus

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
EM-9662 ●*	OPEN	1/20	115	0.85	1550	5/16" x 3.00"	REV.	MA1009
EM-9656 ●*	OPEN	1/15	208-230	0.48	1550	5/16" x 3.00"	REV.	MA1010
SS368	OPEN	1/20	115	1.80	1550	5/16" x 2-3/4"	CCWSE	RMT-0011
SS369	OPEN	1/20	208-230	0.90	1550	5/16" x 2-3/4"	CCWSE	RMT-0012
RMT0004 ●	T.E.	34W	115	1.60	1550	Hubless	CCWSE	NU-34-45-2/1543
RMT0005 ●	T.E.	34W	230	0.80	1550	Hubless	CCWSE	NU-34-45-4/1542
RMT0062 ●	O.O.S.E.	1.5	575-3Ø	2.50	860	5/8" x 2-1/2"	REV.	43846, 43424
MA1074 ●	T.E.	2	575-3Ø	3.10	1140	5/8" x 3.00"	REV.	RMT-0064



276



981



OTC6001 - OTC6004



EM-1779P - EM-1775P




9487



OTC1862 - OTC1864

Tecumseh

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
276	OPEN	50W	230	0.85	1550	5/16" x 2-1/2"	CCWLE	810M050A62, TFM502
981	OPEN	1/15	460	0.60	1550	5/16" x 2-1/2"	CCWLE	810G037A47, 810G050A49
OTC6001	OPEN	1/15	230	0.30	1550	5/16" x 2-3/4"	CCWLE	810S050A99
EM-1779P *	OPEN	1/15	230	0.62	1625	5/16" x 3.00"	CCWLE	TFM502, 810E050A85, F48HXDEJ1779
9487	OPEN	1/12	230	1.30	1500	5/16" x 2-1/8"	CWLE	TFM262
OCT6004	OPEN	1/20	230	1.10	1550	5/16" x 2-1/2"	CCWLE	810S037B01, R2372
EM-1775P*	OPEN	1/20	230	0.50	1500	5/16" x 3.00"	CCWLE	F48DEF1775, TFM372, 810E037A84
OTC1862 ●*	OPEN	1/4	230	1.90	1625	1/2" x 2-3/4"	CWLE	TFM1862
OTC1864 ●*	OPEN	1/4	460	0.95	1625	1/2" x 2-3/4"	CWLE	TFM1864



954 - 9608



955



UE955



680A



5FE1056S - 5FE1054S - 5FE1076S



5BD1076 - 5BD1106 - EM-2553



H955L



UEH955



SS9193

Trane

Stock #	Encl.	HP	Volt	Amps	RPM	Shaft		
954 *	OPEN	1/30	115	0.60	1100/3	1/2" x 8-1/2"	CWLE	MOT-1878, MOT-1875
9608 *	OPEN	1/20	115	0.60	1100/3	1/2" x 9-7/8"	REV.	MOT-1875, X70500149-02
955 *	OPEN	1/6	115	2.00	1500/3	10-1/2" x 1/2" x 10-1/2"	CWLE	MOT-1979, MOT-482
UE955 *	OPEN	1/6	115	2.30	1500/3	10-1/2" x 1/2" x 10-1/2"	DBL	MOT-1979, MOT-482
680A *	OPEN	1/8	115	1.50	775/3	11-1/2" x 1/2" x 11-1/2"	CCWLE	MOT-711
5FE1056S ●*	T.E.A.O.	1/2	575	1.20	1100	1/2" x 6-1/2"	REV.	D2752
5FE1054S ●*	T.E.A.O.	1/2	575	1.40	1625	1/2" x 6-1/2"	REV.	D2750
5FE1076S ●*	T.E.A.O.	3/4	575	1.90	1075	1/2" x 6-1/2"	REV.	D2753, MOT-2607
5BD1076 ●*	OPEN	3/4	575	2.30	1075/2	1/2" x 5.00"	REV.	F34575DD, 21A309661P01
5BD1106 ●*	OPEN	1	575	2.40	1075/2	1/2" x 5.00"	REV.	F1575DD, X70671181-017 X70671479-001
H955L ●	OPEN	3	575-3Ø	3.60	1800	7/8" x 2.30"	REV.	F31853, MOT-6769 MOT-9800
UEH955 ●	OPEN	3	575-3Ø	3.40	1800	7/8" x 2.30"	REV.	F31853, MOT-6769 MOT-9800
SS9193 ●*	OPEN	1	575	2.20	1075	5/8" x 5-31/32"	REV.	X70671655-01, MOT09193



SS7738



OYK1056V1



H953V1



UEH953 - UEH955



H955L

York

Stock #	Encl.	HP	Volts	Amps.	RPM	Shaft	Rotation	Replaces
SS7738 ●*	T.E.A.O.	1/2	460	1.50	1075	1/2" x 6.00"	REV.	YCM124SD, 024-24100-002
OYK1056V1 *	T.E.A.O.	1/2	208-230	2.50	1090	1/2" x 4.00"	CWLE	024-24110-701, 713
5BD1076 ●*	OPEN	3/4	575	2.30	1075/2	1/2" x 5.00"	REV.	F34575DD, 024-31946-003
EM-2553 *	OPEN	1	460	3.30	1100/3	1/2" x 4.00"	REV.	YEFM1460, 024-21671-000 024-21673-000
H953V1 ●	OPEN	2	575-3Ø	2.40	1800	7/8" x 2.30"	REV.	F21853, 024-19623-007
UEH953 ●	OPEN	2	575-3Ø	2.70	1725	7/8" x 2-1/4"	REV.	F21853, 024-19623-007
H955L ●	OPEN	3	575-3Ø	3.60	1800	7/8" x 2.30"	REV.	F31853, 024-19623-009
UEH955 ●	OPEN	3	575-3Ø	3.40	1800	7/8" x 2.30"	REV.	F31853, 024-19623-009

● Ball Bearing (*) P.S.C. Design




Features:


- Open Drip-Proof
- Class 'B' Insulation
- Reversible Rotation
- 60 Hz.
- Resilient Base
- Thermally Protected
- 1/2" to 5/8" Sleeve & Key Included
- Self-Aligning Sleeve & Sealed Ball Bearings



All US Motors Models



All OmniDrive Models



48 Frame - Single Speed


OMNIDRIVE®



Formerly A.O. Smith Electrical Products Company

Stock #	Encl.	HP	Volts	Amps.	RPM	"A" Dim.	Shaft	Rotation
SS933	OPEN	1/4	115	4.80	1725	6.81"	1/2" x 1.50"	REV.
SS934	OPEN	1/3	115	6.60	1725	6.81"	1/2" x 1.50"	REV.
SS935	OPEN	1/2	115	8.30	1725	7.76"	1/2" x 1.50"	REV.
SS934B ●	OPEN	1/3	115	6.60	1725	6.81"	1/2" x 1.50"	REV.
SS935B ●	OPEN	1/2	115	7.60	1725	6.81"	1/2" x 1.50"	REV.
SS933D ●	OPEN	1/4	115/208-230	4.60/2.20-2.10	1725	6.75"	1/2" x 1.88"	REV.
SS934D ●	OPEN	1/3	115/208-230	6.60/3.40-3.10	1725	6.75"	1/2" x 1.88"	REV.
SS935D ●	OPEN	1/2	115/208-230	7.60/3.70-3.80	1725	8.58"	1/2" x 1.88"	REV.
SS936D ●^	OPEN	3/4	115/208-230	11.60/5.90-5.80	1725	10.55"	5/8" x 1.88"	REV.
GF2024	OPEN	1/4	115	5.40	1725	7.50"	1/2" x 1.50"	REV.
GF2034	OPEN	1/3	115	6.80	1725	7.80"	1/2" x 1.50"	REV.
GF2054	OPEN	1/2	115	8.00	1725	8.30"	1/2" x 1.50"	REV.
RB2024 ●	OPEN	1/4	115	5.00	1725	7.80"	1/2" x 1.50"	REV.
RB2034 ●	OPEN	1/3	115	6.00	1725	7.50"	1/2" x 1.50"	REV.
BF2054 ●	OPEN	1/2	115/208-230	8.20/4.10	1725	8.30	1/2" x 1.50"	REV.

(^) 56 Frame



48 Frame - Single Speed



Formerly Emerson Motors


Stock #	Encl.	HP	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
EM-840CV ●	OPEN	1/4	115	4.80	1725	9.40"	1/2" x 1.60"	REV.
EM-841CV ●	OPEN	1/3	115	6.40	1725	9.90"	1/2" x 1.60"	REV.
EM-1542C ●	OPEN	1/2	115	7.80	1725	9.90"	1/2" x 1.60"	REV.

56Z Frame - Two Speed

Stock #	Encl.	HP	Volts	Amps.	RPM	"C" Dim.	Shaft	Rotation
EM-5793C ●	OPEN	1/3	115	6.40	1725/1140	10.40"	1/2" x 1.50"	REV.
EM-5794C ●	OPEN	1/2	115	8.70	1725/1140	10.40"	1/2" x 1.50"	REV.
EM-5795C ●	OPEN	3/4	115	11.50	1725/1140	11.30"	1/2" x 1.50"	REV.

Features:

- Open Drip-Proof
- Class 'A' and 'B' Insulation
- Reversible Rotation
- Resilient Base
- 5/8" Diameter Shaft
- 40°C Ambient
- High Starting Torque
- Sleeve and Ball Bearings



All Century Models



All US Motors Models

56 Frame



Stock #	Encl.	HP	Volts	Amps.	RPM	"C" Dim.	Rotation
C455	O.D.P.	1/3	115 / 208-230	6.60 / 3.00 - 3.30	1725	11.10"	REV.
C403 ●	O.D.P.	1/3	115 / 208-230	6.60 / 3.00 - 3.30	1725	11.10"	REV.
C607	O.D.P.	1/2	115 / 208-230	9.00 / 4.00 - 4.50	1725	11.10"	REV.
C412V1 ●	O.D.P.	1/2	115 / 208-230	9.00 / 4.00 - 4.50	1725	11.10"	REV.
C654	O.D.P.	3/4	115 / 208-230	5.40 - 5.50 / 11.00	1725	11.10"	REV.
C426V1 ●	O.D.P.	3/4	115 / 208-230	5.40 - 5.50 / 11.00	1725	11.10"	REV.
C692	O.D.P.	1	115 / 208-230	6.20 - 6.30 / 12.60	1725	11.40"	REV.
C523V1 ●	O.D.P.	1	115 / 208-230	6.20 - 6.30 / 12.60	1725	11.90"	REV.
C621 ●	O.D.P.	1-1/2	115 / 208-230	7.80 - 7.50 / 15.00	1725	12.70"	REV.
D13CA2JH9 ●	O.D.P.	1/3	115 / 208-230	8.80 / 3.90 - 4.40	1725	9.80"	REV.
EM-1790 ●	O.D.P.	1/3	115 / 208-230	7.40 / 3.70	1725	9.30"	REV.
EM-1893 ●	O.D.P.	3/4	115 / 208-230	11.40 / 5.70	1725	10.80"	REV.
EM-3187C ●	O.D.P.	1	115 / 230	14.00 / 7.00	1725	11.80"	REV.
EM-4242 ●	O.D.P.	1-1/2	115 / 208-230	22.40 / 11.20	1725	12.80"	REV.

Cross Reference


	Rotom	Emerson	GE	Marathon	Fasco
C455	N/A	N/A	N/A	N/A	N/A
C403	S1120	180	C216	C216	D6082
C607	S1138	N/A	N/A	N/A	N/A
C412V1	S1146	1790	C1153	B317	D6084
C654	S1168	N/A	N/A	N/A	N/A
C426V1	S1174	1893	C1156	B319	D6086
C692	N/A	N/A	N/A	N/A	N/A
C523V1	S1199	3187C	C1158	C1159	D6088
C621	S1336	4242	C1160	C1160	D6090

(●) Ball Bearing



Features:

- Resilient Base and Rigid Base
- Reversible Rotation
- 5/8" Diameter Shaft
- Open Drip-Proof
- 40°C Ambient
- Ball Bearings



56 Frame



Stock #	HP	RPM	Volts	Amps.	Frame	Shaft Dia.	Base
H840	1/2	1800	460/200-230	1.00/1.9-2.0	56	5/8	Resilient
H940V1	1/2	1800	575	0.70	56	5/8	Resilient
H851V2	3/4	1800	460/200-230	1.50/2.8-3.0	56	5/8	Resilient
H941L	3/4	1800	575	0.90	56	5/8	Resilient
H842V1	1	3600	460/200-230	1.80/3.5-3.6	56H	5/8	Resilient
H950	1	3600	575	1.50	56H	5/8	Resilient
H852L	1	1800	460/200-230	2.00/3.7-4.0	56H	5/8	Resilient
H942	1	1800	575	1.50	56H	5/8	Resilient
H882	1	1800	460/200-230	2.00/3.70-4.0	56H	5/8	Rigid
H883	1	1800	460/200-230	1.90/3.5-3.8	56HZ	7/8	Rigid
H843V1	1.5	3600	460/200-230	2.30/4.70-4.6	56H	5/8	Resilient
H944	1.5	3600	575	1.80	56H	5/8	Resilient
H853V2	1.5	1800	460/200-230	2.80/5.0-5.6	56H	5/8	Resilient
H943V1	1.5	1800	575	2.00	56	5/8	Resilient
H884L	1.5	1800	460/200-230	2.80/5.0-5.6	56H	5/8	Rigid
H885L	1.5	1800	460/200-230	2.80/5.0-5.6	56HZ	7/8	Rigid
UEH951	1.5	1800	575	2.00	56HZ	7/8	Rigid
UEH885	1.5	1800	200-230/460	5.00/2.50	56HZ	7/8	Rigid
H844	2	3600	460/200-230	2.90/6.0-5.8	56H	5/8	Resilient
H952	2	3600	575	2.40	56H	5/8	Resilient
H854	2	1800	460/200-230	3.00/6.6-7.0	56HZ	7/8	Resilient
UEH886	2	1800	460/200-230	7.60-7.8/3.9	56HZ	7/8	Rigid
UEH953	2	1800	575	2.70	56HZ	7/8	Rigid
H845	3	3600	460/200-230	4.30/9.0-8.6	56HZ	7/8	Resilient
H954	3	3600	575	3.60	56HZ	7/8	Resilient
H980L*	3	1800	208-230/460	9.00-9.0/4.5	56Y	7/8	Rigid
H855L	3	1800	460/200-230	4.40/9.0-8.8	56HZ	7/8	Resilient
UEH887	3	1800	460/200-230	4.60/9.0-9.2	56HZ	7/8	Rigid
UEH955	3	1800	575	3.40	56HZ	7/8	Rigid
H847	5	3600	460/200-230	6.60/13.4-13.2	56HZ	7/8	Rigid
H956	5	3600	575	5.40	56HZ	7/8	Rigid
H979L*	5	1800	208-230/460	15.00/7.40	56Y	7/8	Rigid

Features:

- Open Drip-Proof
- Rigid Base
- Class 'F' Insulation - Class 'B' Rise at Service Factor
- Reversible Rotation
- 1.15 Service Factor
- F-1 Assembly
- Aluminum End-Shields with Steel Inserts
- Light Weight Rolled Steel Frame
- Suitable for use with Inverters (VFD)
- Double Shielded Bearings (140 - 280 Frame)
- Lifting Provisions (210 Frame & Up)
- Regreasable Bearings (180 Frame & Up)
- Ball Bearings
- Shaft Grounding Kits Available



42/36 Month Warranty *




Three Phase

Stock #	HP	Volts	Amps.	RPM	Frame	Efficiency %
D1P2D	1	208-230/460	3.20/1.50	1800	143T	85.5
D32P2D	1-1/2	208-230/460	4.40/2.20	1800	145T	86.5
D2P2D	2	208-230/460	5.90/2.80	1800	145T	86.5
D3P2D	3	208-230/460	8.40-7.80/3.90	1800	182T	89.5
D5P2D	5	208-230/460	13.80-13.00/6.50	1800	184T	89.5
D7P2D	7-1/2	208-230/460	20.20-18.50/9.30	1800	213T	91.0
D10P2D	10	208-230/460	26.30-23.80/11.90	1800	215T	91.7
D15P2D	15	208-230/460	40.00-37.00/18.30	1800	254T	93.0
D20P2D	20	208-230/460	54.00-49.00/24.40	1800	256T	93.0
D25P2D	25	208-230/460	64.00-58.00/29.00	1800	284T	93.6
D30P2D	30	208-230/460	77.00-69.00/34.00	1800	286T	94.1
D1P2G	1	575	1.30	1800	143T	85.5
D32P2G	1-1/2	575	1.70	1800	145T	86.5
D2P2G	2	575	2.20	1800	145T	86.5
D3P2G	3	575	3.20	1800	182T	89.5
D5P2G	5	575	5.20	1800	184T	89.5
D7P2G	7-1/2	575	7.20	1800	213T	91.0
D10P2G	10	575	9.80	1800	215T	91.7
D15P2G	15	575	14.80	1800	254T	93.0
D20P2G	20	575	19.20	1800	256T	93.0
D25P2G	25	575	23.00	1800	284T	94.1
D30P2G	30	575	27.70	1800	286T	94.1

(* Note: Warranty Period is 42 Months from Date of Manufacture or 36 Months from Date of Installation on Sine Wave Power or 30 Months from Date of Manufacture or 24 Months from Date of Installation on VFD Power, whichever occurs first.

Features:

- Aluminum Construction
- Totally Enclosed Fan Cooled
- **3600 RPM**
- Continuous Duty
- Class 'B' Insulation
- Removable Bolt-on Feet
- Reversible
- 40°C Ambient
- UL Listed & CSA Approved
- 3 Positions for Feet Allow for
- F-1, F-2, F-0 Conduit Box Location
- Inverter Duty 10:1 V.T. / 2:1 C.T.
- Ball Bearings
- 1.15 S.F.




56 & 56HZ Frame

OMNIDRIVE®

Stock #	HP	Volts	Amps.	"C" Dim	Shaft (Dia.)	Frame
WA631	1/3	208-230/460	1.26-1.14/0.57	12.67"	5/8	56
WA611	1/3	575	0.46	12.67"	5/8	56
WA632	1/2	208-230/460	1.82-1.64/0.82	12.67"	5/8	56
WA612	1/2	575	0.66	12.67"	5/8	56
WA633	3/4	208-230/460	2.59-2.34/1.17	12.67"	5/8	56
WA613	3/4	575	0.94	12.67"	5/8	56
WA634	1	208-230/460	3.24-2.92/1.46	13.66"	5/8	56H
WA614	1	575	1.17	13.66"	5/8	56H
TA624	1	208-230/460	3.24-2.92/1.16	14.02"	7/8	56HZ
TA604	1	575	1.17	14.02"	7/8	56HZ
WA635	1-1/2	208-230/460	4.71-4.26/2.13	13.66"	5/8	56H
WA615	1-1/2	575	1.70	13.66"	5/8	56H
TA625	1-1/2	208-230/460	4.71-4.26/2.13	14.02"	7/8	56HZ
TA605	1-1/2	575	1.70	14.02"	7/8	56HZ
WA636	2	208-230/460	6.02-5.44/2.72	13.66"	5/8	56H
WA616	2	575	2.18	13.66"	5/8	56H
TA626	2	208-230/460	6.02-5.44/2.72	14.02"	7/8	56HZ
TA606	2	575	2.18	14.02"	7/8	56HZ
WA637	3	208-230/460	8.76-7.92/3.96	13.66"	5/8	56H
WA617	3	575	3.17	13.66"	5/8	56H
TA627	3	208-230/460	8.70-7.96/3.96	14.02"	7/8	56HZ
TA607	3	575	3.17	14.02"	7/8	56HZ

Features:

- Aluminum Construction
- Totally Enclosed Fan Cooled
- **1800 RPM**
- Continuous Duty
- Class 'B' Insulation
- Removable Bolt-on Feet
- Reversible
- 40°C Ambient
- UL Listed & CSA Approved
- 3 Positions for Feet Allow for F-1, F-2, F-0 Conduit Box Location
- Inverter Duty 10:1 V.T. / 2:1 C.T.
- Ball Bearings
- 1.15 S.F.




56 & 56HZ Frame

OMNIDRIVE®

Stock #	HP	Volts	Amps.	"C"	Shaft (Dia.)	Frame
WA681	1/3	208-230/460	1.43-1.30/0.65	12.67"	5/8"	56
WA661	1/3	575	0.52	12.67"	5/8"	56
WA682	1/2	208-230/460	2.12-1.92/0.96	12.67"	5/8"	56
WA662	1/2	575	0.77	12.67"	5/8"	56
WA683	3/4	208-230/460	2.94-2.66/1.33	12.67"	5/8"	56
WA663	3/4	575	1.06	12.67"	5/8"	56
WA684	1	208-230/460	3.84-3.48/1.74	13.66"	5/8"	56H
WA664	1	575	1.39	13.66"	5/8"	56H
TA674	1	208-230/460	3.84-3.48/1.74	14.02"	7/8"	56HZ
TA654	1	575	1.39	14.02"	7/8"	56HZ
WA685	1-1/2	208-230/460	5.28-4.78/2.39	13.66"	5/8"	56H
WA665	1-1/2	575	1.91	13.66"	5/8"	56H
TA675	1-1/2	208-230/460	5.28-4.78/2.39	14.02"	7/8"	56HZ
TA655	1-1/2	575	1.91	14.02"	7/8"	56HZ
WA686	2	208-230/460	6.73-6.08/3.04	13.66"	5/8"	56H
WA666	2	575	2.43	13.66"	5/8"	56H
TA676	2	208-230/460	6.73-6.08/3.04	14.02"	7/8"	56HZ
TA656	2	575	2.43	14.02"	7/8"	56HZ

Features:

- Aluminum Construction
- Totally Enclosed Fan Cooled
- **3600 RPM**
- Continuous Duty
- Class 'B' Insulation
- Removable Bolt-on Feet
- Reversible
- 40°C Ambient
- UL Listed & CSA Approved
- 3 Positions for Feet Allow for
- F-1, F-2, F-0 Conduit Box Location
- Inverter Duty 10:1 V.T. / 2:1 C.T.
- Ball Bearings
- 1.15 S.F.





56 & 56HZ Frame

OMNiDRIVE®

Stock #	HP	Volts	Amps.	"C"	Shaft (Dia.)	Frame
WA631C	1/3	208-230/460	1.26-1.14/0.57	12.67"	5/8	56
WA611C	1/3	575	0.46	12.67"	5/8	56
WA632C	1/2	208-230/460	1.82-1.64/0.82	12.67"	5/8	56
WA612C	1/2	575	0.66	12.67"	5/8	56
WA633C	3/4	208-230/460	2.59-2.34/1.17	12.67"	5/8	56
WA613C	3/4	575	0.94	12.67"	5/8	56
WA634C	1	208-230/460	3.24-2.92/1.46	13.66"	5/8	56H
WA614C	1	575	1.17	13.66"	5/8	56H
TA624C	1	208-230/460	3.24-2.92/1.16	14.02"	7/8	56HZ
TA604C	1	575	1.17	14.02"	7/8	56HZ
WA635C	1-1/2	208-230/460	4.71-4.26/2.13	13.66"	5/8	56H
WA615C	1-1/2	575	1.70	13.66"	5/8	56H
TA625C	1-1/2	208-230/460	4.71-4.26/2.13	14.02"	7/8	56HZ
TA605C	1-1/2	575	1.70	14.02"	7/8	56HZ
WA636C	2	208-230/460	6.02-5.44/2.72	13.66"	5/8	56H
WA616C	2	575	2.18	13.66"	5/8	56H
TA626C	2	208-230/460	6.02-5.44/2.72	14.02"	7/8	56HZ
TA606C	2	575	2.18	14.02"	7/8	56HZ
WA637C	3	208-230/460	8.76-7.92/3.96	13.66"	5/8	56H
WA617C	3	575	3.17	13.66"	5/8	56H
TA627C	3	208-230/460	8.70-7.96/3.96	14.02"	7/8	56HZ
TA607C	3	575	3.17	14.02"	7/8	56HZ

Features:

- Aluminum Construction
- Totally Enclosed Fan Cooled
- **1800 RPM**
- Continuous Duty
- Class 'B' Insulation
- Removable Bolt-on Feet
- Reversible
- 40°C Ambient
- UL Listed & CSA Approved
- 3 Positions for Feet Allow for F-1, F-2, F-0 Conduit Box Location
- Inverter Duty 10:1 V.T. / 2:1 C.T.
- Ball Bearings
- 1.15 S.F.



56C & 56HCZ Frame

OMNIDRIVE®

Stock #	HP	Volts	Amps.	"C"	Shaft (Dia.)	Frame
WA681C	1/3	208-230/460	1.43-1.30/0.65	12.67"	5/8"	56C
WA661C	1/3	575	0.52	12.67"	5/8"	56C
WA682C	1/2	208-230/460	2.12-1.92/0.96	12.67"	5/8"	56C
WA662C	1/2	575	0.77	12.67"	5/8"	56C
WA683C	3/4	208-230/460	2.94-2.66/1.33	12.67"	5/8"	56C
WA663C	3/4	575	1.06	12.67"	5/8"	56C
WA684C	1	208-230/460	3.84-2.48/1.74	13.66"	5/8"	56HC
WA664C	1	575	1.39	13.66"	5/8"	56HC
TA674C	1	208-230/460	3.84-2.48/1.74	14.02"	7/8"	56HCZ
TA654C	1	575	1.39	14.02"	7/8"	56HCZ
WA685C	1-1/2	208-230/460	5.28-4.78/2.39	13.66"	5/8"	56HC
WA665C	1-1/2	575	1.91	13.66"	5/8"	56HC
TA675C	1-1/2	208-230/460	5.28-4.78/2.39	14.02"	7/8"	56HCZ
TA655C	1-1/2	575	1.91	14.02"	7/8"	56HCZ
WA686C	2	208-230/460	6.73-6.08/3.04	13.66"	5/8"	56HC
WA666C	2	575	2.43	13.66"	5/8"	56HC
TA676C	2	208-230/460	6.73-6.08/3.04	14.02"	7/8"	56HCZ
TA656C	2	575	2.43	14.02"	7/8"	56HCZ



Features:

- Totally Enclosed Construction
- Cast Iron Construction
- Three Year Warranty
- Dual Mounting Holes
- Cast Iron Gasketed Conduit Box
- Double Lip Seal on Both Ends
- Class 'F' Insulation - Class 'B' Temp. Rise
- NEMA MG 1, EEMAC M1-6, CSA C390
- Double Sealed 'ZZ' Bearings up to (215T Frame)
- Standard (Non-Metric) Hardware
- F-2 Field Convertible
- Conduit Box can be Rotated 90 Degrees
- Ground Lug in Conduit Box
- Rust Preventative Treated Steel Fan Cover
- VPI Insulation System
- 'C' Face Kits Available
- 20:1 V.T. / 10:1 C.T.
- Inverter Duty
- Regreasable Bearings (254T Frame & Up)
- Oversized Ball Bearings



All Models



Three Phase

Stock #	HP	Volts	Volts	RPM	Frame	Efficiency %	C Face Kit
TCP657 •	3	575	3.10	1800	182T	87.5	CFP18
TCP658 •	5	575	5.20	1800	184T	87.5	CFP18
TCP659 •	7.5	575	7.50	1800	213T	89.5	CFP21
TCP65A •	10	575	10.00	1800	215T	89.5	CFP21
TCP65B •	15	575	14.00	1800	254T	91.0	CFP25
TCP65C •	20	575	19.60	1800	256T	91.0	CFP25
TCP65D •	25	575	23.60	1800	284T	92.4	CFP28
TCP65E •	30	575	28.30	1800	286T	92.4	CFP28
TCP65F •	40	575	37.00	1800	324T	93.0	CFP32
TCP65G •	50	575	46.30	1800	326T	93.0	CFP32
TCP677 •	3	208-230/460	7.4/3.7	1800	182T	87.5	CFP18
TCP678 •	5	208-230/460	12.2/6.1	1800	184T	87.5	CFP18
TCP679 •	7.5	208-230/460	18.2/9.1	1800	213T	89.5	CFP21
TCP67A •	10	208-230/460	24.2/12.1	1800	215T	89.5	CFP21
TCP67B •	15	208-230/460	35.8/17.9	1800	254T	91.0	CFP25
TCP67C •	20	208-230/460	47.4/23.7	1800	256T	91.0	CFP25
TCP67D •	25	208-230/460	57.6/28.8	1800	284T	92.4	CFP28
TCP67E •	30	208-230/460	69/34.5	1800	286T	91.0	CFP28

Features:

- Open Drip-Proof
- Single Phase & Three Phase
- Mounting Bracket
- 1800 RPM
- Permanently Sealed Ball Bearings
- Replacements for OEM Motors such as Armstrong (A), Bell & Gossett (B) & Taco (T)

Type '2A' 4.67" B.C.D. fits # 2 Bearing Assembly
 Type '2B' 5.00" B.C.D. fits # 3 & 4 Bearing Assembly
 Type '2C' 5.875" B.C.D. fits # 5, 6 & 7 Bearing Assembly



Type 2A & 2B



Type 2C



Type 2C

Single Phase

OMNIDRIVE®	Stock #	HP	Volts	Amps.	Type	Bearing	Rotation	Replaces
	SS1350	1/12	115	2.5	2A	BALL	CWSE	R1350
	SS1355	1/6	115	3.8	2A	BALL	CWSE	---
	SS1352	1/6	115	3.8	2B	BALL	CWSE	R1352
	SS1354	1/4	115	4.6	2B	BALL	CWSE	R1354
	SS1444	1/4	115	4.6	2C	BALL	CCWSE	R1444
	SS1356	1/3	115	6.0	2B	BALL	CWSE	R1356
	SS1446	1/3	115	6.0	2C	BALL	CCWSE	R1446
	SS1459	1/2	115-208/230	5.7/3.0-2.9	2C	BALL	REV.	R1459
	SS1462	3/4	115-208/230	8.2/4.7-4.2	2C	BALL	REV.	R1462
	C245^	1	230/115	6.5/13.0	4	BALL	REV.	R1463

(^) Round Body - No Bracket



Three Phase

OMNIDRIVE®	Stock #	HP	Volts	Amps.	Type	Bearing	Rotation	Replaces
	UEH1041	1/2	208-230/460	2.12-1.92/.96	3	Ball	REV.	R1368, H1041L
	UEH1046	1/2	575	0.77	3	Ball	REV.	R1369, H1046L
	UEH1042	3/4	208-230/460	2.94-2.66/1.33	3	Ball	REV.	R1370, H1042L
	UEH1047	3/4	575	1.06	3	Ball	REV.	R1372, H1047L
	UEH1043	1	208-230/460	3.23-2.92/1.46	3	Ball	REV.	R1371, H1043L
	UEH1048	1	575	1.17	3	Ball	REV.	R1373, H1048L
	UEH1044	1.5	208-230/460	4.72-4.27/2.14	3	Ball	REV.	R1374, H1044L
	UEH1049	1.5	575	1.71	3	Ball	REV.	R1375, H1049L

OPTIDRIVE E2 - Single Phase

Digital control for Single Phase motors - AC Variable Speed Drive 0.5-1.5 HP (115V & 240V Ratings)

The Optidrive E2 Single Phase is the world's first fully digital, fully packaged variable speed drive for controlling low power single phase motors. Designed to be cost effective and easy to use, the Optidrive E2 Single Phase is for use with PSC (Permanent Split Capacitor) or Shaded-Pole Single-Phase induction motors. Optidrive E2 Single Phase uses a revolutionary motor control strategy to achieve reliable intelligent starting of single phase motors. Optidrive E2 Single Phase has only 14 standard parameters to adjust in its basic form. The Optidrive's legendary ease of use ensures quick and easy drive commissioning. For the more advanced user the extended parameter set gives access to powerful additional functionality.

Typically used for direct-drive fans and blowers with PSC (permanent-split capacitor) and shaded pole motors on single-phase power. These are typically applications with a starting torque of between 50-100% of motor full load rated torque.



OPTIDRIVE E2 - Single Phase IP66/NEMA 4X Enclosure

Digital control for Single Phase motors - AC Variable Speed Drive 0.5-1.5 HP (115V & 240V Ratings)

All the same features & performance as above plus:

- Local potentiometer for speed control
- Drive FWD/OFF/REV switch - Programmable for Hand / Auto (Local / Remote) applications
- Built-In Disconnect - Provides the ability to isolate the motor for maintenance and servicing.



OPTIDRIVE E2 - Three Phase IP20 Enclosure

Ease of Use - AC Variable Speed Drive 0.5-15 HP (115V, 240V & 480V Ratings)

Rich in features the Optidrive E2 is the most commercially competitive Optidrive in the Optidrive family. Innovative and compact the Optidrive E2 range combines good looks with robustness, reliability and easy to use performance. The product is dedicated to low power applications where total costs are ultra-competitive, including: Competitive purchase price, Low installation costs, Low commissioning costs & Low technical support costs. Optidrive E2 has only 14 standard parameters to adjust in its basic form, thus Optidrive's legendary ease of use could not be easier or quicker to get started with.



OPTIDRIVE E2 - Three Phase IP66/NEMA 4X Enclosure

Ideal for washdown applications - AC Variable Speed Drive 0.5-10 HP (115V, 240V & 480V Ratings)

Expanding on the success of the Optidrive E2, IP20 and IP55/NEMA 12 products, the Optidrive E2 IP66/NEMA 4X is ideal for food and beverage as well as pharmaceutical applications. The IP66 / NEMA 4X enclosure is a cost-effective, washdown duty Optidrive for low power situations. Ready for high-pressure washdown, the IP66 / NEMA 4X can mount directly on your processing equipment.



OPTIDRIVE HVAC - Three Phase IP20 Enclosure

AC Variable Speed Drive 1-350 HP (240V, 480V & 600V Ratings)

Optidrive HVAC sets a new standard for dedicated fan & pump control.

Whilst retaining the ease of use traditionally associated with Invertek Drives, Optidrive HVAC has an innovative design, combined with robust performance to provide powerful flow control and reliability in a compact drive. Example savings based on a 45kW load using Optidrive HVAC compared to direct on-line control, an estimated 20% reduction in speed results in potential energy savings of 50%.

The Optidrive HVAC provides powerful and flexible control that is ideal for applications such as centrifugal pumps and fan units, where large and immediate energy savings can almost always be found.

575-600V
NOW
AVAILABLE



OPTIDRIVE HVAC - Three Phase IP55 & IP66 Enclosure

AC Variable Speed Drive 1-350 HP (240V, 480V & 600V Ratings)

All the same features & performance as the OPTIDRIVE HVAC IP20.

575-600V
NOW
AVAILABLE



OPTIDRIVE P2 - Three Phase IP20 Enclosure

AC Variable Speed Drive 1-350 HP (240V, 480V & 600V Ratings)

The all new Optidrive P2 provides world leading control for both standard induction motors and permanent magnet motors.

Open loop vector control of standard induction motors provides up to 200% torque from zero speed. Open and closed loop control of the latest generation of high efficiency PM motors. Closed loop encoder feedback capability for standard induction motors. Extensive I/O and communications interface capabilities ensure the drive can be integrated quickly and efficiently into a wide variety of control systems.

A simple parameter structure and carefully selected factory settings ensure fast and easy commissioning..

575-600V
NOW
AVAILABLE



OPTIDRIVE P2 - Three Phase IP55 & IP66 Enclosure

AC Variable Speed Drive 1-350 HP (240V, 480V & 600V Ratings)

All the same features & performance as the OPTIDRIVE P2 IP20 Enclosure.

- IP55/NEMA 12 'Un-Switched'
- IP66/NEMA 4X 'Switched' includes:
 - Local potentiometer for speed control
 - Drive FWD/OFF/REV switch - Programmable for Hand / Auto (Local / Remote) applications
 - Built-In Disconnect - Provides the ability to isolate the motor for maintenance and servicing.

575-600V
NOW
AVAILABLE



MORE MOTOR KNOWLEDGE... MORE MOTOR EXPERIENCE... MORE MOTOR VARIETY... **AT YOUR SERVICE**

WE'VE ALSO GOT YOU COVERED FOR:



UNIT BEARING MOTORS



ECM REFRIGERATION MOTORS



DC MOTORS



COMPRESSOR DUTY MOTORS



PUMP MOTORS



GENERAL PURPOSE MOTORS (IHP)



ELEVATOR DUTY MOTORS



FARM DUTY MOTORS



MORE DEM REPLACEMENT MOTORS



MORE BLOWERS



MORE 3.3" DIAMETER MOTORS



MORE 4" DIAMETER MOTORS



MORE 5" DIAMETER MOTORS



MORE 48 FRAME MOTORS



MORE 56 FRAME MOTORS



MORE SKELETON MOTORS

INTEGRITY OF CATALOG: The information contained in this catalogue is for reference purposes only. We strive to ensure that the information is as accurate and current as possible. We are in no way responsible for any errors that may arise. We reserve the right to change specifications and other information included without prior notice. If you are concerned about the validity of the information on a certain product, please visit www.uem.ca and contact us.

DISCLAIMER: All content offered from or available in our catalogue are provided to you on an "as is" basis, without representations, warranties or conditions of any kind. You acknowledge and agree that any reliance by you on any information available in this catalogue shall be at your own risk.

All rights reserved. You may not produce, copy, modify or redistribute the design or layout of any Universal Electric Motors content without written permission.

It is important to note that Universal Electric Motors is not affiliated with any of the original equipment manufacturers or their brands which may be referred to herein. Other trade-marks featured in this catalogue are the property of their respective owners. No association between Universal Electric Motors and any trademark holder is expressed or implied. The names, descriptions, numbers and symbols featured throughout this catalogue are for cross reference purposes only.

October 2023

WE DO MOTORS BEST.



www.uem.ca

© Universal Electric Motors. All Rights Reserved.